



Main

Range of product	Acti 9
Product name	Acti 9 iSO
Product or component type	Bell
Device short name	ISO

Complementary

[Us] rated supply voltage	230 V AC 50/60 Hz
Power consumption in VA	5 VA
Mounting mode	Fixed
Mounting support	35 mm symmetrical DIN rail
9 mm pitches	2
Height	81 mm
Width	18 mm
Depth	72 mm
Product weight	77 g
Auxiliary connection terminal	Tunnel type terminals rigid < 4 mm ² Tunnel type terminals flexible < 4 mm ² Tunnel type terminals flexible with ferrule < 4 mm ²
Wire stripping length	12 mm (bottom)
Tightening torque	1.3 N.m bottom

Environment

Noise level	80 dB
Type of sound	Bell
IP degree of protection	IP40 (in modular enclosure) conforming to IEC 60529 IP20 conforming to IEC 60529
Ambient air temperature for operation	-10...40 °C
Ambient air temperature for storage	-25...60 °C

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 0627 - Schneider Electric declaration of conformity
------------------------	---

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

REACH

Reference not containing SVHC above the threshold

Reference not containing SVHC above the threshold
