

## 64634 HLX

Halogen lamps with reflector MR16



### Product features

- Xenon instead of krypton as the filler gas (XENOPHOT HLX versions)
- Luminous flux up to 10 % higher with same power consumption (XENOPHOT HLX versions)



## Technical data

### Electrical data

|                 |          |
|-----------------|----------|
| Nominal voltage | 15.0 V   |
| Nominal wattage | 150.00 W |


### Photometrical data

|                           |        |
|---------------------------|--------|
| Maximum color temperature | 3200 K |
|---------------------------|--------|

### Light technical data

|              |         |
|--------------|---------|
| Focal length | 32.0 mm |
|--------------|---------|

### Dimensions & weight



|          |         |
|----------|---------|
| Diameter | 51.0 mm |
| Length   | 42.0 mm |

### Lifespan

|          |      |
|----------|------|
| Lifespan | 50 h |
|----------|------|

### Additional product data

|                                    |          |
|------------------------------------|----------|
| Coating                            | Dichroic |
| Base (standard designation)        | GZ6.35   |
| Minimum diameter of lamp enclosure | 51.0 mm  |

### Capabilities

|                  |         |
|------------------|---------|
| Dimmable         | Yes     |
| Cooling          | Forced  |
| Burning position | p90/p15 |

Product datasheet

Certificates & standards

|                    |   |
|--------------------|---|
| EEI – Energy Label | B |
|--------------------|---|


Country specific categorizations

|                 |           |
|-----------------|-----------|
| ANSI code       | EFR       |
| LIF             | A1/232    |
| Order reference | 64634 HLX |

Country specific information

| Product code  | METEL code   | SEG-No. | STK number | UK Org |
|---------------|--------------|---------|------------|--------|
| 4050300006819 | OSRH64634HLX | -       | 4739416    | -      |
| 4050300006819 | OSRH64634HLX | -       | 4739416    | -      |

## Product datasheet



### Logistical Data

| Product code  | Product description | Packaging unit<br>(Pieces/Unit) | Dimensions (length<br>x width x height) | Volume               | Gross weight |
|---------------|---------------------|---------------------------------|-----------------------------------------|----------------------|--------------|
| 4050300006819 | 64634 HLX           | Folding carton box<br>1         | 58 mm x 46 mm x<br>46 mm                | 0.12 dm <sup>3</sup> | 35.60 g      |
| 4050300946429 | 64634 HLX           | Shipping carton box<br>20       | 196 mm x 122 mm x<br>153 mm             | 3.66 dm <sup>3</sup> | 788.00 g     |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### References / Links

For further technical information please refer to the following OSRAM brochure:  
“Technology and applications, Low-voltage tungsten-halogen lamps”  
“Halogen lamps, low and medium voltage for entertainment, technical and medical applications” cross reference list

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.