

Greasing Oiling Lubricating

Grease Spray

WIKO GREASE SPRAY guarantees a long-term functional reliability of expensive installations by reducing downtimes and repairs.

Trading units

400 ml can

Item no.:

AFES.D400

Application Areas

- Lubrication of heavily stressed machine parts e.g. slide bearings, ball bearings, hinge supports, shafts and guides in sectors like industry, vehicle construction, shipping
- Perfectly suited as lubrication for battery terminals
- Lubrication of gear wheels, toothed racks, chains and steel cables, open gear mechanisms and driving rods
- Easy to apply product for a long-term lubrication

Characteristics

- Multifunctional grease with high capillary action
- Long-term resistance to water
- Resistant to temperature in a range of - 40°C to + 250°C (short-term)
- Prevents corrosion
- Excellent adhesive strength
- Reduction of down-times and repairs as well as usage of other lubricants

Instructions

The designated surfaces have to be free of dirt, rust, oil and grease (We recommend the usage of a suited WIKO Cleaner). Shake the aerosol can intensively for approx. 2 minutes. Perform a spray sample. Afterwards, apply the spray evenly from a range of 20 to 30 cm and let it air dry approx. 10 minutes. After usage, turn the aerosol can upside-down and spray until only propellant gas emerges out of the nozzle.

