



CorePro LEDtube EM/ Mains

CorePro LEDtube 600mm 8W865

The CorePro LEDtube is an affordable LED solution suitable for replacing T8 fluorescent lamps. The product provides a natural lighting effect for use in general lighting applications, as well as instant energy savings – an environmentally friendly solution.

Product data

General Information	
Cap-Base	G13 [Medium Bi-Pin Fluorescent]
Main Application	Industrial
Nominal Lifetime (Nom)	30000 h
Switching Cycle	200000X
B50L70	30000 h

Light Technical	
Colour Code	865 [CCT of 6500K]
Luminous Flux (Nom)	800 lm
Luminous Flux (Rated) (Nom)	800 lm
Colour Temperature, horizontal (Nom)	6500 K
Color Consistency	<6
Colour Rendering Index horiz (Nom)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %

Operating and Electrical	
Input Frequency	50 to 60 Hz
Power (Rated) (Nom)	8 W
Lamp Current (Nom)	38 mA

Starting Time (Nom)	0.5 s
Warm Up Time to 60% Light (Nom)	0.5 s
Power Factor (Nom)	0.9
Voltage (Nom)	220-240 V

Temperature	
T-Ambient (Max)	45 °C
T-Ambient (Min)	-20 °C
T-Storage (Max)	65 °C
T-Storage (Min)	-40 °C
T-Case Maximum (Nom)	40 °C

Controls and Dimming	
Dimmable	No

Mechanical and Housing	
Product Length	600 mm

Approval and Application	
Energy Efficiency Label	A+

CorePro LEDtube EM/Mains


Energy Saving Product	Yes
Approval Marks	CE marking RoHS compliance KEMA Keur certificate
Energy Consumption kWh/1000 h	8 kWh
Product Data	
Full product code	871869671105700
Order product name	CorePro LEDtube 600mm 8W865

EAN/UPC - Product	8718696711057
Order code	71105700
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	929001338702
Net Weight (Piece)	0.120 kg

Warnings and Safety

· -



Dimensional drawing



TLED 2ft 8-18W 800lm 6500K G13 Ess-Corep

Product	D1	D2	A1	A2	A3
CorePro LEDtube 600mm 8W865	25.7 mm	28 mm	588.5 mm	595.5 mm	602.5 mm

Photometric data




LEDtube 600mm 8W G13 865 800lm

LEDtube 1500mm 20W G13 840 2200lm


CorePro LEDtube EM/Mains

Photometric data




LEDtube HF 1500mm SO 25 W /865 T8

Lifetime



LEDtube 1500mm 20W G13 840 2200lm



LEDtube 1500mm 20W G13 840 2200lm

