



### Main

|                           |               |
|---------------------------|---------------|
| Range of product          | PratiKa       |
| Product or component type | Wander socket |
| Device short name         | PratiKa screw |
| Plug, socket category     | Low voltage   |
| Poles description         | 3P + N + E    |
| Network type              | AC            |
| Outlet standard           | Industrial    |

### Complementary

|                                     |                                                  |
|-------------------------------------|--------------------------------------------------|
| Plug, socket, control station shape | Straight                                         |
| [In] rated current                  | 32 A                                             |
| [Ue] rated operational voltage      | 380...415 V                                      |
| Network frequency                   | 50/60 Hz                                         |
| Ground lug clockwise position       | 6 h                                              |
| Plug, socket material               | Self-extinguishing engineering polymer housing : |
| Contacts material                   | Brass sleeves :                                  |
| Connections - terminals             | Captive screws                                   |
| Cable cross section                 | 2.5...10 mm <sup>2</sup>                         |
| Cable outer diameter                | 11.5...21 mm                                     |
| Cable entry                         | Cable gland<br>Fair lead                         |
| Thread type                         | Pg 21                                            |
| Product weight                      | 0.3 kg                                           |
| Height                              | 106 mm                                           |
| Width                               | 106 mm                                           |
| Depth                               | 172 mm                                           |
| Colour                              | Grey ( RAL 7035 )                                |
| Voltage colour                      | Red                                              |

### Environment

|                                       |                                                    |
|---------------------------------------|----------------------------------------------------|
| Standards                             | IEC 60309-1<br>IEC 60309-2                         |
| IP degree of protection               | IP44 conforming to IEC 60529                       |
| IK degree of protection               | IK08 conforming to EN 62262                        |
| Fire resistance                       | 850 °C conforming to IEC 60695-2-1                 |
| Relative humidity                     | 90 % ( 20 °C )<br>70 % ( 30 °C )<br>50 % ( 40 °C ) |
| Ambient air temperature for operation | -25...40 °C<br>35 °C ( 86400 s )                   |