



Main

Range of product	Acti 9
Product name	Acti 9 iTR
Product or component type	Transformer
Device short name	ITR
Transformer type	Bell transformer

Complementary

[Ue] rated operational voltage	230 V AC 50/60 Hz
Output voltage	8/12 V: +/- 15 % on load 12/16 V: off load
Output short-circuit protection	Built-in
Rated power in VA	4 VA
Mounting mode	Fixed
Mounting support	35 mm symmetrical DIN rail
9 mm pitches	4
Height	89 mm
Width	36 mm
Depth	60 mm
Colour	White
Auxiliary connection terminal	Tunnel type terminalsrigid 2.5 mm ² Tunnel type terminalsflexible 2.5 mm ² Tunnel type terminalsflexible with ferrule 2.5 mm ²
Wire stripping length	6 mm
Tightening torque	0.5 N.m

Environment

Standards	EN 61558-2-6 IEC 61558-2-6 EN 60742
Product certifications	NF
IP degree of protection	IP20 conforming to IEC 60529
Overvoltage category	Class II with terminal shields in option

Ambient air temperature for operation	-20...55 °C
Ambient air temperature for storage	-25...80 °C

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Under investigation
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------