

A9K23120

miniature circuit breaker - iK60N - 1P - 20 A - B
curve



A9K23120 nav aizst#ts. L#dzu, sazinieties ar savu klientu speci#lists, lai ieg#tu vair#k inform#cijas.

ⓘ P#rtraukts

Main

Device application	Distribution
Range	Acti 9
Product name	Acti 9 iK60
Product or component type	Miniature circuit-breaker
Device short name	IK60N
Poles description	1P
Number of protected poles	1
[In] rated current	20 A 30 °C
Network type	AC
Trip unit technology	Thermal-magnetic
Curve code	B
Breaking capacity	6000 A Icn 230 V AC 50/60 Hz EN/IEC 60898-1
Suitability for isolation	Yes EN/IEC 60898-1
Standards	EN/IEC 60898-1

Complementary

Network frequency	50/60 Hz
Magnetic tripping limit	3...5 x In
[Ics] rated service breaking capacity	6000 A 100 % EN/IEC 60898-1 - 230 V AC 50/60 Hz
Limitation class	3 EN/IEC 60898-1
[Ui] rated insulation voltage	440 V AC 50/60 Hz EN/IEC 60898-1
[Uimp] rated impulse withstand voltage	4 kVEN/IEC 60898-1
Contact position indicator	No
Control type	Toggle
Local signalling	ON/OFF indication
Mounting mode	Clip-on
Mounting support	DIN rail
9 mm pitches	2

Height	85 mm
Width	18 mm
Depth	78,5 mm
Net weight	100 g
Colour	White
Mechanical durability	20000 cycles
Electrical durability	10000 cycles
Locking options description	Padlocking device
Connections - terminals	Single terminal top or bottom) 1...25 mm ² rigid
Wire stripping length	14 mm top or bottom
Tightening torque	2 N.m top or bottom
Earth-leakage protection	Without

Environment

IP degree of protection	IP20 IEC 60529
Pollution degree	2 EN/IEC 60898-1
Overvoltage category	III
Ambient air temperature for operation	-25...60 °C
Ambient air temperature for storage	-40...85 °C

Offer Sustainability

RECh regula	RECh deklarācija
Nesatur RECh SVHC	Jā
ES RoHS direktīva	Under investigation
Nesatur dzīvsudrabu	Jā
Informācija par RoHS izņēmumiem	Jā
Ķīnas RoHS regula	Ķīnas RoHS deklarācija Produkts neietilpst Ķīnas RoHS ietvaros. Vietas deklarācijai informatīva nozīme.
Vides informācijas publiskošana	Produkta ietekme uz vidi
Cirkularitātes profils	Nav jāveic īpašas darbības, lai nodotu otrreizējai pārstrādei
WEEE	Eiropas Savienības tirgū no šī produkta ir jāatbrīvojas, ievērojot noteiktu atkritumu savākšanas kārtību, un produkts nedrīkst nonākt sadzīves atkritumu tvertnēs.

Contractual warranty

Garantija	18 months
-----------	-----------