XVBC36 INDICATING BANK LENS 250V 10W +OPTIONS





has not been replaced. Please contact your customer care center for more information.

Main

TVI CALL	
Range of product	Harmony XVB Universal
Product or component type	Indicator bank
Beacon or indicator bank unit type	Illuminated unit
Signalling type	Steady
Mounting diameter	70 mm
Component name	XVBC
Material	Polycarbonate
Light source	Bulb not included, blue
Bulb type	Incandescent with BA 15d base Protected LED
[Us] rated supply voltage	<= 250 V

Complementary

Charles		
Main		
Range of product	Harmony XVB Universal	
Product or component type	Indicator bank	
Beacon or indicator bank unit type	Illuminated unit	
Signalling type	Steady	
Mounting diameter	70 mm	
Component name	XVBC	
Material	Polycarbonate	
Light source	Bulb not included, blue	
Bulb type	Incandescent with BA 15d base Protected LED	
[Us] rated supply voltage	<= 250 V	
	<u> </u>	
Complementary Assembly style	Customer assembly, up to 5 units	
Maximum power dissipation in W	7 W	
Connections - terminals	Screw clamp terminals, <= 1 x 1.5 mm² with cable end	
[Ui] rated insulation voltage	250 V conforming to IEC 60947-1	
Nominal voltage limit	0.851.1 Un conforming to IEC 60947-5-1	
[Uimp] rated impulse withstand voltage	IEC 60947-1 4 kV	
CAD overall width	70 mm	
CAD overall height	63 mm	
CAD overall depth	70 mm	
Environment		
Pollution degree	2	
Product certifications	GOST UL 508 CSA C22-2 No 14 CCC	
Dec 42, 2040		
Doc 12, 2010		

Environment

		2
Pollution degree	2	,
Product certifications	GOST UL 508	,
	CSA C22-2 No 14 CCC	E. augustus et augustus et Lieu
	· · · · · · · · · · · · · · · · · · ·	7

Standards	EN/IEC 60947-5-1
Protective treatment	TC
Ambient air temperature for storage	-4070 °C
Ambient air temperature for operation	-2550 °C: LED -2570 °C: incandescent
Electrical shock protection class	Class I on support tube conforming to IEC 61140 Class II on base unit conforming to IEC 61140
IP degree of protection	IP65 on fixing base XVBZ0. conforming to IEC 60529 IP66 on base unit conforming to IEC 60529
NEMA degree of protection	NEMA 4X conforming to UL 508 (indoor)

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months