



## Main

Range of product	Acti 9
Product name	Acti 9 iTR
Product or component type	Transformer
Device short name	ITR
Transformer type	Bell transformer

## Complementary

[Ue] rated operational voltage	230 V AC 50/60 Hz
Output voltage	12/24 V: +/- 15 % on load 16/32 V: off load
Output short-circuit protection	Built-in
Rated power in VA	25 VA
Mounting mode	Fixed
Mounting support	35 mm symmetrical DIN rail
9 mm pitches	6
Height	89 mm
Width	54 mm
Depth	60 mm
Colour	White
Auxiliary connection terminal	Tunnel type terminals rigid 2.5 mm <sup>2</sup> Tunnel type terminals flexible 2.5 mm <sup>2</sup> Tunnel type terminals flexible with ferrule 2.5 mm <sup>2</sup>
Wire stripping length	6 mm
Tightening torque	0.5 N.m

## Environment

Standards	EN 60742 EN 61558-2-6 IEC 61558-2-6
Product certifications	NF
IP degree of protection	IP20 conforming to IEC 60529
Overvoltage category	Class II with terminal shields in option

Ambient air temperature for operation	-20...55 °C
Ambient air temperature for storage	-25...80 °C

### Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

### Contractual warranty

Warranty	18 months
----------	-----------