

Technical Data	
Material	Polyethylene
Shrinking ratio	3:1
Operating range	-45°C~+125°C
Longitudinal Shrinkage	≤8%
Standard color	Black
Certificate	UL, RoHS Halogen free
Tool	Heat gun, oven

Part No.	Size		As Supplied mm	After Recoverymm		Standard Packing
	Inch	mm	I.D. Min.	I.D. Max.	W.T. Nom.	m/spool
MSBG3-3.2	1/8	3.2	3.2	1	1	200
MSBG3-4.8	3/16	4.8	4.8	1.6	1.1	100
MSBG3-6.4	1/4	6.4	6.4	2	1.2	100
MSBG3-7.9	5/16	7.9	7.9	2.7	1.4	100
MSBG3-9.5	3/8	9.5	9.5	3.2	1.4	50
MSBG3-12.7	1/2	12.7	12.7	4.2	1.7	1.22m/pcs
MSBG3-19.1	3/4	19.1	19.1	5	1.8	1.22m/pcs
MSBG3-25.4	1	25.4	25.4	6.3	2	1.22m/pcs
MSBG3-30.0	1-1/4	30	30	10.2	2.2	1.22m/pcs
MSBG3-39.0	1-1/2	39	39	13.5	2.4	1.22m/pcs
MSBG3-50.8	2	50	50	17	2.7	1.22m/pcs
MSBG3-64.0	2-1/2	64	64	21	3	1.22m/pcs
MSBG3-75.0	3	75	75	25	3.2	1.22m/pcs
MSBG3-90.0	3-1/2	90	90	30	3.3	1.22m/pcs
MSBG3-100.0	4	100	100	34	3.5	1.22m/pcs
MSBG3-125.0	5	125	125	42	3.5	1.22m/pcs