

CAT. N° 0 342 13

**CONNECTION STRIP NYLBLOC - CAPACITY 6 MM<sup>2</sup> - MAX. CURRENT 41 A - BLACK**

Pack (number of units)	10
Volume (dm <sup>3</sup> )	0,306
Weight (g)	267,00

**Product characteristics****Nylbloc connection strips**

- 12 elements with captive screws
- Supplied with screws undone
- Flame retardant polypropylene (– 25 °C to + 100 °C)
- Ambient temperature from – 25 °C to + 55 °C (T 55)
- Conform to EN 60998-2-1 and EN 60664-1
- Self-extinguishing to EN 60695-2-11 at 850
- Insulation voltage: 250 V according to EN 60 998-2-1
- Use at 400 V integrated in a series of products that comply with the requirements of EN 60664-1, pollution degree 2, overload category III
- Black
- Rated capacity : 6 mm<sup>2</sup>
- Hole Ø : 3.5 mm
- Max current : 41 A

**General characteristics****Nylbloc™ - connection strips and connectors without screws****Documentation****Catalogue pages & additional information**

- [Description page \(p.630\)](#)

**Agreements & certificates of conformity**

- KEMA - 2171325.02
- NF - 650672A
- VDE - 40018574
- IMQ - EN641
- AENOR - 030/000810