

CAT. N° 0 489 59



## PIR IP40/IP65 CEILING-MOUNTING LIGHTING MANAGEMENT SENSOR FOR 1 CIRCUIT - 360°

Pack (number of units)	1
Volume (dm <sup>3</sup> )	1,676
Weight (g)	257,00

### Product characteristics

#### Ideal for high ceiling areas

#### PIR IP 40/IP 65 ceiling-mounting Lighting Management sensor, 360°

- Suitable for low temperature environments (-30° C to +35° C)
- Range Ø40 m
- IP 40 without gasket, IP 65 with gasket
- Consumption 0.85 W
- Maximum installation height: 20m
- Can be installed on surface with dedicated installation accessory included in the box (Cat.No 0 489 65 or 0 489 66)

### General characteristics

#### Lighting Management sensors for 1 circuit - Lighting Management sensors for passage areas with natural light

- Check presence and natural light level continuously, switch off when there is sufficient natural light
- Occupancy mode (automatic switch-on/off factory setting)
- Can be used with push-button Cat.No 0 770 40 (or illuminated push-button Cat.No 0 770 33) for vacancy mode (manual switch-on and manual or automatic switch-off)
- Precise on-site adjustment using configuration tool Cat.No 0 882 30
- Adjustable time delay: 5 s to 59 min
- Light level threshold adjustable from 5 to 1275 lux

### Documentation

#### Catalogue pages & additional information

- [Selection chart \(p.659\)](#)
- [Description page \(p.663\)](#)
- [Motion sensors and Lighting Management sensors for controllers](#)
- [Lighting management stand-alone sensors](#)

#### Installation & technical data

- [S000105276EN-01](#)

#### Installation instructions & related documents

- [LE10633AC](#)