

Description

For use as a switch disconnecter in all types of circuits.

Complies with:
IEC 60947-3 for all ratings
and to EN60669 for ratings from 16A to 63A

Technical data

Utilisation category AC22A 230V / 400V

- In: 16A to 40A frame size 1.
- Connection capacity:
16mm² - rigid conductor
10mm² - flexible conductor



SFT232



SFB125



SFH125

Description	Characteristics	Frame size	Width in 17.5mm	Pack qty.	Cat. ref.
Centre OFF changeover switch I-0-II and common point on top					
	1 x 25A - 230V AC	1	1	12	SFT125
	1 x 32A - 230V AC	1	1	12	SFT132
	1 x 40A - 230V AC	1	1	12	SFT140
	2 x 25A - 230V AC	1	2	6	SFT225
	2 x 32A - 230V AC	1	2	6	SFT232
	2 x 40A - 230V AC	1	2	6	SFT240
	3 x 40A - 400V AC	1	3	4	SFT340
	4 x 40A - 230V AC	1	4	3	SFT440
Centre OFF changeover switch I-0-II and common point on bottom					
	1 x 16A - 230V AC	1	1	12	SFB116
	1 x 25A - 230V AC	1	1	12	SFB125
	1 x 32A - 230V AC	1	1	12	SFB132
	2 x 16A - 230V AC	1	2	6	SFB216
	2 x 25A - 230V AC	1	2	6	SFB225
	2 x 32A - 230V AC	1	2	6	SFB232
Changeover switch I-II and common point on top					
	1 x 25A - 230V AC	1	1	12	SFH125
	1 x 32A - 230V AC	1	1	12	SFH132
	2 x 25A - 230V AC	1	2	6	SFH225
	2 x 32A - 230V AC	1	2	6	SFH232
Changeover switch I-II and common point on bottom					
	1 x 16A - 230V AC	1	1	12	SFL116
	1 x 25A - 230V AC	1	1	12	SFL125
	1 x 32A - 230V AC	1	1	12	SFL132
	2 x 16A - 230V AC	1	2	6	SFL216
	2 x 25A - 230V AC	1	2	6	SFL225
	2 x 32A - 230V AC	1	1	6	SFL232
Changeover switch I-II					
	1 x 25A - 230V AC	1	1	12	SFM125
	1 x 32A - 230V AC	1	1	12	SFM132