



Supply busbars and distribution blocks


SUPPLY BUSBARS FROM 63 TO 90 A

| • I _{sc} peak 17 kA  | Length | Universal 1-pole + neutral or 1-pole | Single pole for auxiliary | 2-pole | 2-pole balanced on 3-phase | 3-pole | 3-pole for 1.5 module/pole MCBs | 3-pole for auxiliary | 4-pole |
|--|-------------|--------------------------------------|---------------------------|-------------|----------------------------|----------|---------------------------------|----------------------|--------|
| | Prong-type | | | | | | | | |
| 1 row | 4 049 26/28 | - | 4 049 38 | 4 049 40/66 | 4 049 42 | - | - | 4 049 44 | |
| meter | 4 049 37 | 4 049 33 | 4 049 39 | 4 049 41 | 4 049 43 | - | 4 049 34 | 4 049 45 | |
| Fork-type | | | | | | | | | |
| 1 row | 4 049 11 | - | 4 049 13 | 4 049 15/67 | 4 049 17 | 4 049 87 | - | 4 049 19 | |
| meter | 4 049 12 | 4 049 09 | 4 049 14 | 4 049 16 | 4 049 18 | - | 4 049 10 | 4 049 20 | |


DISTRIBUTION TERMINAL BLOCKS FROM 63 TO 100 A

| • I _{sc} peak 10 kA  | Number of outputs | Bar terminal blocks | | Insulated terminal blocks IP 2X (XXB) | | |
|---|-------------------|---------------------|------------|---------------------------------------|----------|-------|
| | | with screws | on support | black | blue | green |
| 4 | 0 048 01 | 0 048 20 | 0 048 50 | 0 048 40 | 0 048 30 | |
| 6 | | | 0 048 16 | 0 048 15 | | |
| 8 | 0 048 03 | 0 048 22 | 0 048 52 | 0 048 42 | 0 048 32 | |
| 12 | | 0 048 24 | 0 048 54 | 0 048 44 | 0 048 34 | |
| 14 | 0 048 05 | | | | | |
| 16 | | 0 048 25 | | 0 048 45 | 0 048 35 | |
| 19 | 0 048 06 | | | 0 048 46 | 0 048 36 | |
| 21 | | 0 048 26 | | | | |
| 24 | 0 048 07 | | | | | |
| 33 | | 0 048 28 | | 0 048 48 | 0 048 38 | |


MODULAR DISTRIBUTION BLOCKS FROM 40 TO 250 A

| • I _{sc} peak 14.5 to 42 kA  | Admissible maximum rating (A) | 2-pole | | | 4-pole | | | Terminal blocks IP 2X | | |
|---|-------------------------------|--|------------------|----------|--|-----------------------------------|----------|-----------------------|---------|--------------------|
| | | Number and section of flexible conductors (mm ²) | | | Number and section of flexible conductors (mm ²) | | | Additional outputs | | |
| | | Cat.Nos | Inputs | Outputs | Cat.Nos | Inputs | Outputs | Earth | Neutral | (mm ²) |
| 40 | 0 048 81 | 2 x 10 | 11 x 4 | 0 048 85 | 2 x 10 | 11 x 4 | 0 048 34 | 0 048 44 | 12 x 6 | |
| 100 | 0 048 80 | 2 x 16 | 5 x 10 | 0 048 84 | 2 x 16 | 5 x 10 | 0 048 32 | 0 048 42 | 8 x 6 | |
| 125 | 0 048 82 | 2 x 25 | 2 x 16 + 11 x 10 | 0 048 88 | 2 x 25 | 2 x 25 + 11 x 10 | 0 048 35 | 0 048 45 | 16 x 6 | |
| | | | | 0 048 86 | 2 x 25 | 2 x 16 + 7 x 10 | 0 048 34 | 0 048 44 | 12 x 6 | |
| | | | | 0 048 76 | 1 x 35 | 1 x 25 + 1 x 16 + 14 x 10 | 0 048 36 | 0 048 46 | 21 x 6 | |
| 160 | | | | 0 048 79 | 1 x 70 | 2 x 25 + 4 x 16 + 8 x 10 | 0 048 35 | 0 048 45 | 16 x 6 | |
| 250 | | | | 0 048 77 | 1 x 120 | 1 x 35 + 2 x 25 + 2 x 16 + 6 x 10 | | | | |

SINGLE POLE MODULAR DISTRIBUTION BLOCKS AND DISTRIBUTION TERMINALS FROM 125 TO 250 A

| • I _{sc} peak 27 to 60 kA  | Admissible maximum rating (A) | Cat.Nos | Number and section of conductors per pole (mm ²) | |
|---|-------------------------------|----------------------------------|--|--------------------------|
| | | | Inputs | Outputs |
| 125 | | 0 048 71 | 4 x 35 | 12 x 10 |
| 160 | | 0 048 83 | 1 x 50 (flexible bar 13 mm max.) | 3 x 25 + 2 x 16 + 7 x 10 |
| | | 0 048 67 (distribution terminal) | Direct into the downstream terminal | 6 x 25 |
| 250 | | 0 048 73 | 1 x 120 (flexible bar 16 mm max.) | 6 x 25 + 4 x 10 |
| | | 0 048 68 (distribution terminal) | Direct into the downstream terminal | 4 x 35 + 2 x 25 |

POWER DISTRIBUTION BLOCKS FROM 125 TO 400 A

| • I _{sc} peak 20 to 75 kA  | Admissible maximum rating (A) | Extra-flat | | Stepped | | |
|---|-------------------------------|--|-------------------------------------|--|---|---|
| | | Number and section of conductors per pole (mm ²) | | Number and section of conductors per pole (mm ²) | | |
| | | Cat.Nos | Inputs | Outputs | Cat.Nos | Inputs |
| 125 | 0 374 47 | 1 x 35 | 10 x 16 (Ph) 17 x 16 (N) | 0 373 95 | 4 bars 12 x 4 mm receiving 5 connectors 2 x 10 each | |
| | | | | 0 374 30 | 1 x 35 | 5 x 25 |
| 160 | | | | 0 374 31 | 1 x 70 | 5 x 35 |
| 250 | 0 374 00 | 1 x 150 | 1 x 70 or 1 x 50 + 1 x 35 or 2 x 35 | 0 374 35 | 1 x 120 | 5 x 50 |
| 400 | | | | 0 373 08 | 2 x Ø8.5 mm | 21 holes M6 70 mm ² max. connectors |
| | | | | 0 374 42 | 2 x 185 | 15 holes M6 15 holes M8 |