



OPTIMUM

SAVINGS,

ENHANCED

AIRTIGHTNESS,

OPTIMUM SPACE FOR

WIRING

- Improve occupants' comfort and the internal air quality.
- Optimum savings by combining blanking plates with Ecobatibox boxes.
- Enhanced airtightness thanks to flexible entries wide enough for spiral conduits. Wide flange, retractable gripping clamps.
- Optimum wiring space. Opening entries made easier by the detachable tab.
- Double cable entries
 - small one for flexible cables (Ø4 to 9 mm)
 - bigger one for spiral conduits

ECOBATIBOX, LOWER ENERGY CONSUMPTION

Eliminate uncontrolled air infiltration and cut the building's energy bills.

Modular Ecobatibox boxes and membranes which remain flexible in any climate can stop energy losses between the electrical panel and the wiring accessory.



Boxes available with 1, 2, 3 and 4 gangs.
Depth 40 or 50 mm.



0 800 21



0 800 34



Installation **see e-catalogue**

Pack	Cat.Nos		1-gang boxes
40 25	Depth 40 0 800 21	Depth 50 0 800 31	For 1 gang or 2 modules Drilling diameter 67 mm For wiring accessories using screws or claws Can be associated with blanking plate kits Cat.Nos 0 800 16/20
15 30	Depth 40 0 800 22	Depth 50 0 800 32	Multi-gang boxes For wiring accessories using screws Drilling diameter: 67 mm For 71 mm fixing centers Supplied with 1 removable divider for accommodating extended functions (ex.: preterminated sockets) Can be associated with blanking plate kits Cat.Nos 0 800 16/20 For 2-gang or 4/5 modules Horizontal or vertical use
10	0 800 23	0 800 33	For 3-gang or 6/8 modules Horizontal or vertical use
10	0 800 24	0 800 34	For 4-gang or 8/10 modules Horizontal or vertical use
5	0 893 11		Box for residential environments 4-face box: - 2 faces with 7 x Ø16, 5 x Ø20 and 1 x Ø25 - 2 faces with 6 x Ø16, 3 x Ø20, 1 x Ø25 and 1 x Ø32 Dimensions: 200 x 200 x 85 mm Autoextinguibility: 850°/5 s Fixing with screws, pins or staples Closing of lid by ¼ turn Can also be used with false ceiling and raised floors
10	Depth 40 0 800 84	Depth 50	Junction box For 1-gang mechanisms Drilling diameter: 85 mm Supplied with square lid 100 x 100 mm
20	0 800 16		Blanking plate kits For corrugated conduits Contribute to stopping air leakage regarding the electrical installation To be associated with Ecobatibox boxes for optimum efficiency
20	0 800 20		Ø16 mm
20	0 800 25		Ø20 mm
20	0 800 30		Ø25 mm
			Ø32 mm