


OPTIMUM
SAVINGS,
ENHANCED
AIRTIGHTNESS,
OPTIMUM SPACE FOR
WIRING

- Improve occupants' comfort and the internal air quality.
- Optimum savings by combining blanking plates with Ecobatibox boxes.
- Enhanced airtightness thanks to flexible entries wide enough for spiral conduits. Wide flange, retractable gripping clamps.
- Optimum wiring space. Opening entries made easier by the detachable tab.
- Double cable entries
 - small one for flexible cables (Ø4 to 9 mm)
 - bigger one for spiral conduits

ECOBATIBOX, LOWER ENERGY CONSUMPTION

Eliminate uncontrolled air infiltration and cut the building's energy bills.

Modular Ecobatibox boxes and membranes which remain flexible in any climate can stop energy losses between the electrical panel and the wiring accessory.



Boxes available with 1, 2, 3 and 4 gangs.
Depth 40 or 50 mm.



0 800 21

0 800 34


 Installation **see e-catalogue**

Pack	Cat.Nos			
40 25	Depth 40	Depth 50	1-gang boxes For 1 gang or 2 modules Drilling diameter 67 mm For wiring accessories using screws or claws Can be associated with blanking plate kits Cat.Nos 0 800 16/20	
	0 800 21	0 800 31		
15 30	Depth 40	Depth 50	Multi-gang boxes For wiring accessories using screws Drilling diameter: 67 mm For 71 mm fixing centers Supplied with 1 removable divider for accommodating extended functions (ex.: preterminated sockets) Can be associated with blanking plate kits Cat.Nos 0 800 16/20 For 2-gang or 4/5 modules Horizontal or vertical use	
	0 800 22	0 800 32		
10	0 800 23	0 800 33	For 3-gang or 6/8 modules Horizontal or vertical use	
10	0 800 24	0 800 34	For 4-gang or 8/10 modules Horizontal or vertical use	
5	0 893 11		Box for residential environments 4-face box: - 2 faces with 7 x Ø16, 5 x Ø20 and 1 x Ø25 - 2 faces with 6 x Ø16, 3 x Ø20, 1 x Ø25 and 1 x Ø32 Dimensions: 200 x 200 x 85 mm Autoextinguibility: 850°/5 s Fixing with screws, pins or staples Closing of lid by ¼ turn Can also be used with false ceiling and raised floors	
10	Depth 40	Depth 50	Junction box For 1-gang mechanisms Drilling diameter: 85 mm Supplied with square lid 100 x 100 mm	
	0 800 84			
20			Blanking plate kits For corrugated conduits Contribute to stopping air leakage regarding the electrical installation To be associated with Ecobatibox boxes for optimum efficiency	
	0 800 16			Ø16 mm
	0 800 20			Ø20 mm
	0 800 25			Ø25 mm
20	0 800 30		Ø32 mm	