Product data sheet Characteristics

PME1WU2B-GR

APC Essential SurgeArrest 1 Outlet 2 USB Ports Black 230V Germany



C)ν	e	rv	ie	W

		.≚
Lead time	Usually in Stock	licat
		Ω.
		σ.

Physical

Physical		u u
Colour	Black	
Depth	4 cm	, s
Height	9.32 cm	7
Net weight	0.13 kg	
Width	6.31 cm	-

Input

Input power	4000 W	
Network frequency	50/60 Hz	
Plug standard	Schuko CEE 7/7P	
Maximum input current	16 A	
Input voltage	220 V	
, -	230 V	
	240 V	

Output

Number of power socket outlets	1	;
Outlet standard	Schuko CEE 7	

Conformance

Product certifications	CE	
Marking	CE Mark	2

Environmental

Ambient air temperature for operation	040 °C
Relative humidity	095 %

Operating altitude	010000 ft
Ambient air temperature for storage	-1545 °C
Storage altitude	0.0015240.00 m

Surge Protection and Filtering

Response time	1 ns common mode
Common mode rejection	45 dB
Peak current	15 kA normal mode
Surge energy rate	680 J

Packing Units

3	
Package 1 Weight	0.17 kg
Package 1 Height	10 cm
Package 1 width	9 cm
Package 1 Length	6.8 cm
SCC14	10731304347016
Number of Units in Package 2	12
Package 2 Weight	2.35 kg
Package 2 Height	127.00 mm
Package 2 width	279.40 mm
Package 2 Length	279.40 mm
Number of Units in Package 3	1008
-	

Offer Sustainability

EU RoHS Directive	Under investigation