



Heat shrinkable tubing 3:1 in a kit

ShrinKit 321 Universal Basic

With ShrinKit 321 HellermannTyton has set a new standard in heat shrink tubing: ShrinKit tubings cover many applications with their ideal shrink ratio of 3:1.

Features and benefits

- Compact and handy kit
- Black and coloured tubing
- Available in a wide size range of 3 mm to 18.0 mm
- 177 precut pieces in five sizes
- Case can be re-used for storing nails, screws, nuts, fish hooks, etc.



ShrinKit 321 Universal Basic.



Heat Shrinkable Tubing 3:1

MATERIAL	Polyolefin, cross-linked (PO-X)
Shrink Ratio	3:1
Operating Temperature	-55 °C to +135 °C
Min. Shrink Temperature	+90 °C
Longitudinal Change After Shrinkage	+5 %/-10 % max.
Dielectric Strength	20 kV/mm according to ASTM D 2671
Flammability	self-extinguishing
Insulation Class	B (VDE 0530)



COMP.	Supplied Ø D min.	Recov. Ø d max.	Length (L)	Wall (WT)	Colour	Content	Tools	Article-No.
1	12.0	4.0	35.0	0.70	Black (BK)	12 pcs.	30-32	380-03005
2	6.0	2.0	80.0	0.70	Blue (BU)	5 pcs.		
	6.0	2.0	80.0	0.70	Red (RD)	5 pcs.		
	6.0	2.0	80.0	0.70	White (WH)	5 pcs.		
	12.0	4.0	80.0	0.70	Black (BK)	2 pcs.		
	12.0	4.0	80.0	0.70	Blue (BU)	2 pcs.		
	12.0	4.0	80.0	0.70	Red (RD)	2 pcs.		
3	6.0	2.0	35.0	0.70	Blue (BU)	10 pcs.		
	6.0	2.0	35.0	0.70	Red (RD)	10 pcs.		
	6.0	2.0	35.0	0.70	White (WH)	10 pcs.		
4	9.0	3.0	35.0	0.70	Green-Yellow (GNYE)	15 pcs.		
5	9.0	3.0	35.0	0.70	Black (BK)	20 pcs.		
6	3.0	1.0	35.0	0.55	Black (BK)	10 pcs.		
	3.0	1.0	35.0	0.55	Blue (BU)	10 pcs.		
	3.0	1.0	35.0	0.55	Red (RD)	10 pcs.		
	3.0	1.0	35.0	0.55	White (WH)	10 pcs.		
7	6.0	2.0	35.0	0.70	Black (BK)	20 pcs.		
	6.0	2.0	35.0	0.70	Green-Yellow (GNYE)	10 pcs.		
8	18.0	6.0	160.0	0.80	Black (BK)	3 pcs.		
	18.0	6.0	160.0	0.80	Green-Yellow (GNYE)	3 pcs.		
	18.0	6.0	160.0	0.80	White (WH)	3 pcs.		

All dimensions in mm. Subject to technical changes.

Recommended Tools			
	30 H5002	31 H5004	32 E4500
	561	561	560

For more information on toolings please refer to the Application Tooling chapter.



For product specific approvals and specifications please refer to the Appendix.