

4 modules box for dry partitions. Dimensions 132.5x71x52 mm

BT-PB504NN | EAN. 8005543772478



Product Line

Box, BTicino

DESCRIPTION

4 modules box for dry partitions (flush mounting in plasterboard, plywood, wood, sheet steel). Dimensions 132,5x71x52 mm

PRODUCT CHARACTERISTICS

- Fixation to the board with large metal clamps
- IP40 protection
- 4 modules
- Color Grey and Yellow
- Packaging 100% plastic free

TECHNICAL CHARACTERISTICS

Mounting method	Hollow wall	Shape	Rectangular
Construction type	Device connection box (round/square)	Model	Single
Provided with revolving ring	No	Couplable	No
Equipped with	None	Length	132 mm
Width	71 mm	Depth (Min-Max)	52-52 mm
Inner depth	50 mm	For number of electric fittings	4
Mounting switching equipment	Screwing	With screws	Yes
Number of non-adjustable device fixing lugs	0	Number of adjustable device fixing lugs	2
Housing feed-through by break- out opening	No	Housing feed-through by seal membrane	Yes
Housing feed-through by nozzle	Yes	Housing feed-through by step membrane	No
For tube diameter	20/25 mm	Suitable for cable diameter (Min-Max)	1-2.5 mm
Pipe locking	No	Pipe locking optional	No
Inlet from the rear	Yes	Number of inlets	6
Number of included spouts	5	Material	Plastic
Halogen free	No	Surface protection	Untreated
Colour	Black	Degree of protection (IP)	IP40
Cover model	None	Transparent cover	No
Cover attachment	Other	Sealable	No

Circuit integrity	None	With screening	No
Air tight	Yes	Max. conductor cross section	2.5 mm ²
Number of poles of the clamp	0	Clamp position fixed	No
Luminaire hook mounting	No	Nozzle	None
Special application	None	With partition panel	No
Compliant with BS 4662	No	degree of impact strength (IK)	IK04
Operating / setting temperature (Min-Max)	-5-40 °C	Storage temperature (Min-Max)	-5-60 °C
Cable support	Not applicable		

THE PRODUCT'S BENEFITS

Installation

Multi-material flush-mounting boxes suitable for refurbishment projects.

Usage

It improves occupant comfort and indoor air quality.

Advantages

- Particularly suitable for low-energy houses.
- Boxes allow to install wiring devices by screws or clamps.

USAGE RECOMMENDATIONS

Indoor use only.

DOCUMENTATION

Agreements & specifications

Agreement

LGJAWLCWLL

| FILE (485 KB)

CAD & design SPECS / BIM

BIM Data

BIM-BTICINO-LIVING-NOW-2026-ENGLISH

| RVT (163.3 MB)

Catalogue pages & other

Catalog Commercial Page

3211578

| PDF (16.1 MB)

Brochure

3252105

| PDF (5.7 MB)

Technical documentation

Technical Sheet

IDP002016_03-EN

| PDF (1.6 MB)