

Multi-outlet extensions with cord

German standard





To connect several devices equipped with plugs with or without earth: appliances class I (simple insulation) or class II (double insulation), lamps, PC, TV, stereo, etc.

Extra-flat (only 30 mm thick): can be slid underneath furniture

Pack	Cat.Nos	Multi-outlet extensions - unswitched	Pack	Cat.Nos	Multi-outlet extensions - switched
	0 •	Wall-mounting possibilities with the packaging accessory 90° socket for connecting a transformer without blocking another socket Power supply cord 1.5 m (3G 1.5 mm²) or 3 m (3G 1.5 mm²) or 5 m (3G 1.5 mm²) and 1.5 mm² or 5 m (3G 1.5 mm²)			On/off switch with a light indicator, can be operated by foot or by hand Socket with child protection shutters tested to withstand 10000 operations Orientable socket outlets Maximum space between 2 sockets to connect transfos, chargers, etc. Supplied with self-gripping tie for grouping the cords of the connected devices
10	White/Grey Black 6 950 01 6 950 10	1.5 m cord 3 x 2P+ ↓			Direct wall-mounting possibilities (with
10	6 950 06 6 950 25				screws) Cable management possible around the
10	6 950 11	5 x 2P+≟			wall-mounting fixtures
10	6 950 16	6 x 2P+±			With power supply cord 1.5 m
10	6 950 02 6 950 15	3 m cord 3 x 2P+±			(3G 1.5 mm²) or 3 m (3G 1.5 mm²) 16 A max Power 3500 W at 230 V
10	6 950 07 6 950 28			White/Grey Black	1.5 m cord
10	6 950 12	5 x 2P+±	5	6 946 21 6 946 01	
10	6 950 17	6 x 2P+±	5	6 946 26 6 946 04	
	· ·	5 m cord	5	6 946 31 6 946 07	
10	6 950 03 6 950 20		5	6 946 36 6 946 09	6 x 2P+↓
10	6 950 08 6 950 30				3 m cord
10	6 950 13	5 x 2P+≟	5	6 946 22 6 946 02	
10	6 950 18	6 x 2P+±	5	6 946 27 6 946 05	
			5	6 946 32	5 x 2P+±
			5	6 946 37	6 x 2P+≟