

Multi-outlet extensions without cord

German standard



6 946 29



7 824 97 + 2 x RJ 45 sockets Cat.No 7 824 24 (p. 543)




6 950 09

Pack	Cat.Nos	Multi-outlet extensions for comfort
		<p>Sockets with child protection shutters tested to withstand 10000 operations</p> <p>Orientable socket outlets</p> <p>To be equipped with flexible cable of 3G 1.5 mm² or 3G 1mm² minimum</p> <p>On/off switch with a light indicator, can be operated by foot or by hand</p> <p>Maximum space between 2 sockets to connect transformers, chargers, etc.</p> <p>Direct wall-mounting possibilities (with screws)</p> <p>Possibility to manage the cable around the feet</p> <p>Supplied with self-gripping tie for grouping the cords of the connected devices</p> <p>16 A max. power 3500 W at 230 V</p>
	<div style="display: flex; justify-content: space-around;"> <div style="text-align: center;"> White/Grey </div> <div style="text-align: center;"> Black </div> </div>	
5	6 946 24 6 946 03	3 x 2P+⊕
5	6 946 29 6 946 06	4 x 2P+⊕
5	6 946 34 6 946 08	5 x 2P+⊕
5	6 946 39 6 946 10	6 x 2P+⊕

Pack	Cat.Nos	Standard extensions for comfort
		<p>To connect several devices equipped with plugs with or without earth: appliances class I (simple insulation) or class II (double insulation), lamps, PC, TV, stereo, etc.</p> <p>Ultra-flat: can be slid underneath furniture</p> <p>Wall-mounting possibilities with the packaging accessory</p> <p>90° socket for connecting a transformer without blocking another socket</p> <p>16 A max. power 3500 W at 230 V</p> <p>To be equipped with flexible cable of 3G 1.5 mm² or 3G 1mm² minimum</p>
	<div style="display: flex; justify-content: space-around;"> <div style="text-align: center;"> White/Grey </div> <div style="text-align: center;"> Black </div> </div>	
10	6 950 04 6 950 23	3 x 2P+⊕
10	6 950 09 6 950 33	4 x 2P+⊕
10	6 950 14 6 950 38	5 x 2P+⊕
10	6 950 19 6 950 45	6 x 2P+⊕

Pack	Cat.Nos	Equipped workstation
2	7 824 97	<p>Equipped with:</p> <ul style="list-style-type: none"> - 4 x 2P+E German standard socket outlets with shutters - 2 blanking plates for integration of Forix mechanisms



Fluorescent inspection lamps

German standard



0 622 41

Conform to EN 61 242 A 11
3000 W - 230 V~ (cable entirely unrolled) with thermal switch protection (manually resettable)

Pack	Cat.Nos	Fluorescent inspection lamps
		<p>IP 64 - IK 09</p> <p>Supplied with fluorescent tube</p> <p>Class II</p> <p>5 m cable</p> <p>H05 RNF (2 x 1 mm²)</p> <p>8 W - 230 V - with 2P - 10/16 A plug</p> <p>G5 lampholder</p>
1	0 622 40	
1	0 622 41	11 W - 230 V - with 2P - 10/16 A plug
		<p>IP 55</p> <p>With hook - Rubber handle supplied with fluorescent tube, 2G7 lampholder</p>
1	0 622 32	11 W - 230 V with 2P plug - 16 A
1	0 622 33	10 m cable - Class II
		11 W - 24 V with Hypra plug
		10 m cable - Class III