

CAT. N° 0 371 76



TERMINAL BLOCK VIKING 3 - SCREW -FOR CONDUCTOR -1 CONNECT -BARE LOCK -METAL BASE

Pack (number of units)	10
Volume (dm ³)	0,485
Weight (g)	687,00

Product characteristics

For protection conductor

- Metal base

1 connection - bare block

- Colour : -
- Nominal cross-section : 35 mm²
- Capacity – Rigid wire : 2.5 to 50 mm²
- Capacity – Flexible wire with or without ferrules : 4 to 35 mm²
- Pitch : 15 mm

General characteristics

Viking™ 3 terminal blocks with screw connection - for copper cables

- Used to make the electrical connection between 2 flexible copper wires with or without ferrules or 2 rigid copper wires
- 2 areas for automatic insertion bridging combs up to 8 pitch (upper level only for multi-level blocks)
- For rails depth 15 mm, EN 60715 depth 7.5 mm and 15 mm

Documentation



Catalogue pages & additional information

- [Selection chart \(p.324-325\)](#)
- [Description page \(p.328\)](#)
- [Technical page \(p.335\)](#)
- [Viking™ 3 terminal blocks with screw connection](#)



Installation & technical data

- [F00914EN-00](#)
- [F00914EN-01](#)