

Preamplifier | Connection input: 2x (2x RCA) | Connection output: 1x (2x RCA) | 2 Channels | AUX / Phono / Turntable |

General information

Stereo preamp suitable for insertion between turntables and other low-level sources and AUX/line inputs on mixers, amps, stack systems etc. With phono sockets and additional AUX input.

Features

- With additional AUX input

Specifications

Colour:	Black
Material:	Aluminium
Frequency response:	20 Hz - 20 kHz
Power source type:	Mains Powered
Power plug:	Type C (CEE 7/17)
Power adapter cable length:	1.50 m
Sound output:	Stereo
Weight:	320 g
Depth:	80.0 mm
Input voltage:	100 - 240 VAC 50/60 Hz
Height:	40.0 mm
Number of channels:	2 Channels
Input impedance:	47K Ohm
Max. output:	2.6 V / 1 KHz
Input overload margin:	39 dB
RIAA deviation response:	20 Hz - 20 kHz ($\pm 0,5$ dB)
Nominal output:	330 mv / 1 kilo-ohm
Total harmonic distortion (THD):	Less than 0.006%
Input sensitivity:	3.0 mV
Output impedance:	1 kOhm
Connection input:	2x (2x RCA)
Connection output:	1x (2x RCA)
Device power input connection(s):	DC Power Plug
Input current:	0.20 A
Input control:	Phono / AUX / Turntable
Function control:	Manual
Width:	180.0 mm



Sales information

Order code:	AAMP2402BK
Product description:	Preamplifier Connection input: 2x (2x RCA) Connection output: 1x (2x RCA) 2 Channels AUX / Phono / Turntable Manual Black
Packaging:	Giftbox
Brand name:	Nedis



Quantity	LxWxH (mm)			Weight
1	165 mm	60 mm	210 mm	580 g
10	310 mm	215 mm	335 mm	6020 g
20	350 mm	340 mm	445 mm	13080 g

nedis
