

## Satellite Splitter | 5-2400 MHz | 6.5 dB | Number of inputs: 1 | Number of outputs: 2 | Impedance: 75 Ohm | Silver

### General information

2-way splitter in a zinc die-cast housing with satellite DC-power pass and with F-connectors to split a satellite-signal.

### Specifications

|                            |            |
|----------------------------|------------|
| Colour:                    | Silver     |
| Impedance:                 | 75 Ohm     |
| Number of outputs:         | 2          |
| Material:                  | Zinc       |
| Number of inputs:          | 1          |
| Satellite accessory type:  | Splitter   |
| Insertion loss:            | 6.5 dB     |
| Satellite frequency range: | 5-2400 MHz |

### Package contents

Splitter



### Sales information

|                      |  |
|----------------------|--|
| Order code:          | <b>SSPL210ME</b>   |
| Product description: | Satellite Splitter   5-2400 MHz   6.5 dB   Number of inputs: 1   Number of outputs: 2   Impedance: 75 Ohm   Silver |
| Packaging:           | Bulk   |
| Brand name:          | Nedis  |



| Quantity   | LxWxH (mm) |        |        | Weight |
|------------|------------|--------|--------|--------|
| <b>1</b>   | 50 mm      | 20 mm  | 55 mm  | 37 g   |
| <b>100</b> | 210 mm     | 120 mm | 280 mm | 3820 g |
| <b>200</b> | 220 mm     | 255 mm | 305 mm | 7960 g |