BGA Heat Sink - High Performance Cross-Cut Tape On





ATS Part#: ATS-55300D-C1-R0

Description: 30.00 x 30.00 x 9.50 mm BGA Heat Sink - High Performance Cross-Cut Tape On

Heat Sink Type: Cross-cut Heat Sink Attachment: Tape On

Equivalent Part Number: ATS-55300D-C2-R0

*Image above is for illustration purpose only.


Features & Benefits


- High efficiency cross-cut fin design provides low pressure drop characteristics
- Large surface area increases heat sink performance
- Designed for BGAs and surface mount packages
- Comes preassembled with high performance thermal interface material

Thermal Performance

AIR VELOCITY		@200 LFM 1.0 M/S	@300 LFM 1.5 M/S	@400 LFM 2.0 M/S	@500 LFM 2.5 M/S	@600 LFM 3.0 M/S	@700 LFM 3.5 M/S	@800 LFM 4.0 M/S
THERMAL RESISTANCE	Unducted Flow	14 °C/W	NA °C/W					
	Ducted Flow	0	N/A	N/A	N/A	N/A	N/A	N/A

Product Detail





- Dimension C is the heat sink height from the bottom of the base to the top of the fin field.
- ATS-55300D-C2-R0 is the exact heat sink assembly with an equivalent thermal interface material
- Thermal performance data are provided for reference only. Actual performance may vary by
- ATS reserves the right to update or change its products without notice to improve the design or
- ATS certifies that this heat sink assembly is RoHS-6 and REACH compliant.
- Contact ATS to learn about custom options available.

