

Ordering information

Plastic enclosed switch-disconnectors



ONE20M_G



ONE20M_Y



ONE20M_W

Enclosed switch-disconnectors 2, 3 and 4 pole, IP67

The delivery includes a padlockable handle for 3 padlocks (I-O/ON-OFF). Threaded knock out holes for cable entry. Cover is not interlocked. The 2 pole types includes PE terminal. The 3 and 4 pole types include N and PE terminals. Does not include auxiliary contacts. Cable glands included.

Cable entries from top and bottom

| Poles | Rated current | | Cable outlets/side | Dimensions | | | Type | Order number | Weight /unit kg |
|-------|----------------|----------------|--------------------|--------------|-------------|-------------|------|--------------|--------------------|
| | AC-22A 415V | AC-23A 400V | | Height mm | Width mm | Depth mm | | | |

Grey round handle

| | | | | | | | | | |
|---|----|------|---------------|----|----|----|----------|-----------------|-----|
| 2 | 20 | 15.2 | 2xM20 / 2xM20 | 92 | 65 | 84 | ONE20M2G | 1SCA135532R1001 | 0.1 |
| 3 | 20 | 15.2 | | 92 | 65 | 84 | ONE20M3G | 1SCA135535R1001 | 0.1 |
| 4 | 20 | 15.2 | | 92 | 65 | 84 | ONE20M4G | 1SCA135538R1001 | 0.1 |

Red/yellow round handle

| | | | | | | | | | |
|---|----|------|---------------|----|----|----|----------|-----------------|-----|
| 2 | 20 | 15.2 | 2xM20 / 2xM20 | 92 | 65 | 84 | ONE20M2Y | 1SCA135533R1001 | 0.1 |
| 3 | 20 | 15.2 | | 92 | 65 | 84 | ONE20M3Y | 1SCA135536R1001 | 0.1 |
| 4 | 20 | 15.2 | | 92 | 65 | 84 | ONE20M4Y | 1SCA135540R1001 | 0.1 |

White round handle

| | | | | | | | | | |
|---|----|------|---------------|----|----|----|----------|-----------------|-----|
| 2 | 20 | 15.2 | 2xM20 / 2xM20 | 92 | 65 | 84 | ONE20M2W | 1SCA138456R1001 | 0.1 |
| 3 | 20 | 15.2 | | 92 | 65 | 84 | ONE20M3W | 1SCA138457R1001 | 0.1 |
| 4 | 20 | 15.2 | | 92 | 65 | 84 | ONE20M4W | 1SCA138459R1001 | 0.1 |