



Mobiya 170Lumens with 6Hrs backup & water resistant, Mobile charging

AEP-LB01-SU12W

١	Л	а	ı	r	1

Range of product	Mobiya
Product or component type	Portable solar lighting system
Solar panel type	Polycrystalline

Complementary	
[Us] rated supply voltage	524 V DC, solar panel
Bulb type	1 LED (1.2 W)
Power range	2.5 W
Maximum rated voltage	5 V for DC
Luminous flux	170 lm 85 lm 20 lm
Light source colour	Warm white LED, colour temperature: 5000 K
Signalling function	Battery status charging green Battery status full green Battery status low red
Operating time	6 h at 170 lm 12 h at 85 lm 48 h at 20 lm
Kit composition	1 solar panel with cable, cable length: 5 m (AWG 24) 1 Multi port mobile charging cable
Cable cross section	0.20 mm² - AWG 24
Cable length	5 m 2 core cable for between solar panel and DC input
Battery capacity	3 Ah at 3.2 V, LiFePO4
Integrated connection type	DC jack 5 V DC, maximum load current: 400 mA +/- 10 mA USB port
Width	Lamp: 156 mm Solar panel: 142 mm
Depth	Solar panel: 16 mm
Height	Lamp: 142 mm Solar panel: 185 mm
Net weight	0.45 kg LED unit 0.57 kg solar panel

Environment

IP degree of protection	IP65

IEC	
SONCAP SABS	
CE LM-79 LIGHTING GLOBAL	
-1050 °C	
90 %	
	SONCAP SABS CE LM-79 LIGHTING GLOBAL -1050 °C

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	1.3 kg
Package 1 Height	19.6 cm
Package 1 width	18.5 cm
Package 1 Length	19.2 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	8
Package 2 Weight	11.17 kg
Package 2 Height	42 cm
Package 2 width	38.5 cm
Package 2 Length	40 cm
Unit Type of Package 3	P12
Number of Units in Package 3	96
Package 3 Weight	140.0 kg
Package 3 Height	80 cm
Package 3 width	80 cm
Package 3 Length	120 cm

Offer Sustainability

EU RoHS Directive	Under investigation
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Contractual warranty

Warranty	2 years
----------	---------