



精度等级/General	tolerance(mm)
0	>3
~	>6
3	>10
6	>18
10	>30
~	>50
18	>80
30	>120
50	>180
80	>280
120	>315
180	>400
250	>500
315	>500
400	>500
500	>500
±0.12	±0.26
±0.22	±0.51
±0.37	±0.80
±0.93	±1.05
±1.15	±1.60
±2.20	±2.50
±2	±2

UL 标准/UL Standard:	B	C	D
额定电压/电涌/Rated Voltage(V)/Current(A)	3000/10	/	3000/10
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/行架等级/Pollution Degree	III/3	III/2	II/2
额定电压/电涌/Rated Voltage(V)/Current(A)	250/9	320/9	630/9
额定脉冲电压(kV)/Rate Impulse Voltage(kV)	4	4	4
线径范围(导线和导线)/Wire Range(rigid and flexible)(mm ² /AWG)	0.2~1.5/26~16		
间距/Pitch(mm)/极数范围/Poles	5.08/N=02~24P		
引线长度/Stripping length(mm)	10		
使用温度范围/Operating temperature(°C)	-40~+105		
符合RoHS环保要求/Conform to RoHS	Yes		

ITEM	NAME OF PART	MATERIAL	NOTES
7	Spring	Stainless steel	
6	Back Pin Header	Copper alloy	Sn Plated
5	Front Pin Header	Copper alloy	Sn Plated
4	Button	POM	UL94HB
3	Cover	PA66	UL94V-0
2	Housing	PA66	UL94V-0
1	Side Housing	PA66	UL94V-0

MATERIAL:	/
MAT NO.:	/
STATUS:	/
APPD:	LI QL 2020.05.20
CHKD:	/
DRT:	MEK 2017.03.13
NAME:	DEGSON® NINGBO DEGSON ELECTRICAL CO., LTD
DRAWING NO.:	DG246-5.08-C01
TYPE:	CUSTOMER DRAWING

DG246-5.08-XXP-1Y-00A(H)

REV	ECN	DESCRIPTION	DRT	DATE
1				
2				
3				
4				
5				
6				

PCB LAYOUT