

CAT6 Network Cable | RJ45 Male | RJ45 Male | U/UTP | 0.25 m | Round | PVC | White | Label



Product specifications CCGL85200WT025:

|                               |             |           |       |
|-------------------------------|-------------|-----------|-------|
| AWG value                     | 26          | Shielding | U/UTP |
| Cable design                  | Round       | SmartLife | No    |
| Cable length                  | 0.25 m      | Snagless  | No    |
| Cable mantle material         | PVC         |           |       |
| Cable mantle size             | 6.0 mm      |           |       |
| Cable type                    | CAT6        |           |       |
| Colour                        | White       |           |       |
| Conductor material            | Copper      |           |       |
| Connector A                   | RJ45 Male   |           |       |
| Connector B                   | RJ45 Male   |           |       |
| Connector design - side A     | Straight    |           |       |
| Connector design - side B     | Straight    |           |       |
| Connector plating             | Gold Plated |           |       |
| Frequency                     | 250 MHz     |           |       |
| Material                      | PVC         |           |       |
| Maximum bandwith              | 1 Gbps      |           |       |
| Number of products in package | 1 pcs       |           |       |
| Packaging                     | Label       |           |       |

Packaging information:

|                    |                   |
|--------------------|-------------------|
| Brand              | Nedis             |
| Order code         | CCGL85200WT025    |
| EAN single Product | 5412810422975     |
| EAN Inner Carton   | 5412810430321     |
| EAN Outer Carton   | 5412810434848     |
| Packaging          | Label             |
| Package contents   | 1x CAT6 UTP cable |

| Quantity | L x    | W x    | H (mm) | Weight |
|----------|--------|--------|--------|--------|
| 1        | 20 mm  | 225 mm | 60 mm  | 20 g   |
| 160      | 200 mm | 280 mm | 280 mm | 3520 g |
| 320      | 310 mm | 310 mm | 400 mm | 7240 g |

