



PowerWalker VI 1000 LCD

Line-Interactive UPS

1000VA Line-Interactive UPS

2x Schuko outlets, 2x IEC outlets

USB Connection for monitoring

LCD display to show all UPS settings

Built-in boost and buck AVR function



Item-No. 10120018



Product Features

PowerWalker VI 1000 LCD offers longer backup time for business workstation. It provides comprehensive LCD display for users to monitor the powerstatus. With powerful protection, it secures your data loss from power failure, surge, and sags.

- Built-in super smart charger, shorten 50% of charging time
- Excellent microprocessor control guarantees high reliability
- Boost and Buck AVR for voltage stabilization
- Off-mode auto charging
- No load autoshutdown
- Auto-restart while AC is recovering
- Simulated sine wave
- Cold start function
- Built-in USB communication port and RJ-11 phone protection







Technical Details

Product Features

BatteryWeak

Battery faulty

110ddet i edta	
Capacity	1000VA /600W
Input	
Voltage	220/230/240VAC
Voltage Range	160-290VAC
Output	
Voltage	220/230/240VAC
Voltage Regulation	±10% (Battery Mode)
Frequency	50 or 60Hz
Freq. Regulation	±1 Hz (Battery Mode)
Waveform	Modified Sine wave
Transfer Time	
Typical	2-6ms
Battery	
Туре	12V / 7Ah
Quantity	2 x
RechargeTime	4h to 90%
Full Protection	
Discharge	Yes
Overcharge	Yes
Overload	Yes
LCD Display	
LCD Indicators	AC mode, Battery mode, Load level, Battery capacity, Input voltage, Output voltage, Overload alarm, Fault alarm and Low battery alarm.
Audio Indicato	
Battery Mode	Beep every 10sec
Low Battery	Beep every second
Fault	Beep every 0.5sec

Beep every2sec

Continuously sounding

Connections

Communication USB		
Dutlets2x Schuko, 2x IEC		
Protection Port RJ11 in/out		
Software & System Requirements		
Software ViewPower		
Dperating System For details visit: www.powerwalker.com/viewpower.html		
Other 1x USB port		
Product Details		
Dimensions 350mm x 146mm x 165mm (DxWxH)		
Colour Black		
Weight UPS case 8.0kg		
Nodel Code VI 1000 LCD		
Environment		
Environment Temperature 0°C - 40°C		
Temperature0°C – 40°C		
Temperature 0°C – 40°C Humidity 0 - 90% (non-condensing) Package Content PowerWalker VI 1000 LCD,		
Temperature 0°C – 40°C Humidity 0 - 90% (non-condensing) Package Content PowerWalker VI 1000 LCD, Software CD, USB cable, AC inpu		
Temperature 0°C – 40°C Humidity 0 - 90% (non-condensing) Package Content PowerWalker VI 1000 LCD, Software CD, USB cable, AC inpu power cord, printed manual		
Temperature 0°C – 40°C Humidity 0 - 90% (non-condensing) Package Content PowerWalker VI 1000 LCD, Software CD, USB cable, AC inpu power cord, printed manual Logistic Data PowerWalker VI 1000 LCD,		
Temperature 0°C – 40°C Humidity 0 - 90% (non-condensing) Package Content PowerWalker VI 1000 LCD, Software CD, USB cable, AC inpu power cord, printed manual Logistic Data EN/DE/FR/ES/IT/PT/SV/FI/NO/TR RU/UA/BY/PL/CZ/HR/HU/BG/KK/		
Temperature 0°C – 40°C Humidity 0 - 90% (non-condensing) Package Content PowerWalker VI 1000 LCD, Software CD, USB cable, AC inpu power cord, printed manual Logistic Data EN/DE/FR/ES/IT/PT/SV/FI/NO/TR		
Temperature 0°C – 40°C Humidity 0 - 90% (non-condensing) Package Content PowerWalker VI 1000 LCD, Software CD, USB cable, AC inpu power cord, printed manual Logistic Data EN/DE/FR/ES/IT/PT/SV/FI/NO/TR RU/UA/BY/PL/CZ/HR/HU/BG/KK/ Manual Language	SR_	
Temperature 0°C – 40°C Humidity 0 - 90% (non-condensing) Package Content PowerWalker VI 1000 LCD, Software CD, USB cable, AC inpu power cord, printed manual Logistic Data EN/DE/FR/ES/IT/PT/SV/FI/NO/TR RU/UA/BY/PL/CZ/HR/HU/BG/KK/ Manual Language Dimension/Giftbox 445mm x 200mm x 255mm	SR_	
Temperature 0°C – 40°C Humidity 0 - 90% (non-condensing) Package Content PowerWalker VI 1000 LCD, Software CD, USB cable, AC inpu power cord, printed manual Logistic Data EN/DE/FR/ES/IT/PT/SV/FI/NO/TR RU/UA/BY/PL/CZ/HR/HU/BG/KK/S Siftbox Language EN/DE/FR/ES/IT/PT/SV/FI/NO/TR RU/UA/BY/PL/CZ/HR/HU/BG/KK/S	SR_	
Temperature 0°C – 40°C Humidity 0 - 90% (non-condensing) Package Content PowerWalker VI 1000 LCD, Software CD, USB cable, AC inpu power cord, printed manual Logistic Data EN/DE/FR/ES/IT/PT/SV/FI/NO/TR RU/UA/BY/PL/CZ/HR/HU/BG/KK/ Giftbox Language EN/DE/FR/ES/IT/PT/SV/FI/NO/TR RU/UA/BY/PL/CZ/HR/HU/BG/KK/ Dimension/Giftbox 445mm x 200mm x 255mm (DxWxH)	SR_	
Temperature 0°C – 40°C Humidity 0 - 90% (non-condensing) Package Content PowerWalker VI 1000 LCD, Software CD, USB cable, AC inpu power cord, printed manual Logistic Data EN/DE/FR/ES/IT/PT/SV/FI/NO/TR RU/UA/BY/PL/CZ/HR/HU/BG/KK/ Siftbox Language EN/DE/FR/ES/IT/PT/SV/FI/NO/TR RU/UA/BY/PL/CZ/HR/HU/BG/KK/ Dimension/Giftbox 445mm x 200mm x 255mm (DxWxH) Weight/Giftbox 9.0kg	SR_	
Temperature 0°C – 40°C Humidity 0 - 90% (non-condensing) Package Content PowerWalker VI 1000 LCD, Software CD, USB cable, AC inpu power cord, printed manual Logistic Data EN/DE/FR/ES/IT/PT/SV/FI/NO/TR RU/UA/BY/PL/CZ/HR/HU/BG/KK/S Siftbox Language EN/DE/FR/ES/IT/PT/SV/FI/NO/TR RU/UA/BY/PL/CZ/HR/HU/BG/KK/S Dimension/Giftbox 445mm x 200mm x 255mm (DxWxH) Weight/Giftbox 9.0kg	SR_	
Temperature 0°C – 40°C Humidity 0 - 90% (non-condensing) Package Content PowerWalker VI 1000 LCD, Software CD, USB cable, AC inpu power cord, printed manual Logistic Data EN/DE/FR/ES/IT/PT/SV/FI/NO/TR RU/UA/BY/PL/CZ/HR/HU/BG/KK/ Siftbox Language EN/DE/FR/ES/IT/PT/SV/FI/NO/TR RU/UA/BY/PL/CZ/HR/HU/BG/KK/ Dimension/Giftbox 445mm x 200mm x 255mm (DxWxH) Weight/Giftbox 9.0kg Pieces/palette 72	SR_	