

Froduct KCC 2511



KCC-2511 is a crimping tool for coaxial connectors, 10.9 mm, 5.41 mm, 2.54 mm, 1.69 mm/.213", .429", .100", .067", HEX-Crimp.

- High strength, through hardened alloy steel construction
- Unique mechanism significantly reduces hand force requirement over competing crimping tools
- Versatile and easy to customize for right hand or left hand users.
- Non-slip pad holds tool in place when leveraging on a work surface
- Full cycle crimp mechanism to ensure consistent, reliable crimp
- Ratchet release mechanism to clear miscrimps and obstructions
- Precision eccentric adjustment for consistent performance and ability to calibrate
- · Hole in handle allows attachment of safety strap
- Each tool has a unique serial number for traceability





TECHNICAL DATA Length: 256 mm/10.08" Width: 22 mm/0.87" Height: 80 mm/3.15" Weight: 560 gr/1.23 lb Crimp dimensions mm/mm²: 5,41 mm/10,90 mm/2,54 mm/1,69 mm Crimp dimensions inch/AWG: .213"/.429"/.100"/.067 Connector: Coaxial connector Description: For example BNC, TNC, N connectors on RG 58, RG 8, RG 11, Ethernet, Thinnet. Life span, cycles: 50,000 Cables: 9914, RG114A/U, RG115A/U, RG12A/U, RG133A/U, RG142B/U, RG144/U, RG165/U, RG166/U, RG1A/U, RG213/U, RG214/U. RG215/U. RG216/U. RG22/U. RG223/U. RG225/U. RG227/U, RG22B/U, RG26A/U, RG302/U, RG391/U, RG58C/U, RG63B/U, RG65A/U, RG79B/U

Pressmaster AB P.O. Box 3, Industrivägen SE-796 21 Älvdalen, Sweden Tel: +46 (0)251-451 00 info@pressmaster.se www.pressmaster.com