

KEMET Part Number: R71MI33304000K
(71MI33304000K)

Capacitor, Film, Metallized Polypropylene, 0.33 uF, +/-10% Tol, -40/+110C, General Purpose, 420 VDC@105C, Lead Spacing=15 mm



General Information	
Supplier:	KEMET
Dielectric:	Metallized Polypropylene
Application:	General Purpose
Sub Application:	Pulse
Style:	Radial Box
Lead Form:	Wire Leads
Features:	Pulse
RoHS:	Yes

Dimensions (mm)		
Symbol	Dimension	Tolerance
L	18	+0.3
H	12	+0.1
T	6	+0.2
S	15	+/-0.4
LL	30	+5
F	0.6	+/-0.05

Specifications	
Capacitance:	0.33 uF
Voltage:	420 VDC
Tolerance:	+/-10%
Voltage AC:	220 VAC
Rated Temperature:	105C
Temperature Range:	-40/+110C
Dissipation Factor @ 1 kHz:	0.1%
Dissipation Factor @ 10 kHz:	0.1%
Dissipation Factor @ 100kHz:	0.1%
Insulation Resistance:	100 GOhm
Inductance:	10
Maximum dVdT:	160 v/us
Miscellaneous:	Above 105C DC And AC Voltage Derating Is 4%/C

Packaging Specifications	
Package Kind:	Bulk
Package Quantity:	900