
KEMET Part Number: C971U472MUWDCA7317



C900AH SFTY X1-400 Y1-250, Ceramic, 4700 pF, 20%, 400 VAC (X1), 250 VAC (Y1), Y5U, Lead Spacing = 10mm



Dimensions		
D	14mm MAX	
Т	5mm MAX	
S	10mm +/-1mm	
Н0	18mm +2/-0mm	
F	0.55mm +/-0.1mm	

Packaging Specifications		
Packaging:	Ammo	
Packaging Quantity:	500	

General Information	
Supplier:	KEMET
Series:	C900AH SFTY X1-400 Y1-250
Style:	Radial Disc
RoHS:	Yes
Termination:	Tin
Failure Rate:	N/A
Qualifications:	UL, ENEC, VDE, CSA, CAN
Halogen Free:	Yes

Specifications		
Capacitance:	4700 pF	
Capacitance Tolerance:	20%	
Voltage AC:	400 VAC (X1), 250 VAC (Y1)	
Dielectric Withstanding Voltage:	4000 VDC	
Temperature Range:	-40/+125°C	
Temperature Coefficient:	Y5U	
Dissipation Factor:	2.50%	
Insulation Resistance:	10 GOhms	
Safety Class:	X1/Y1	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

