



FOR 客户名称	APPROVED 客户确认签字	ATTN 销售负责人



Bottom View and Contact Composition

Part Number: LAS3F-11 ■/△/▲

"■"	Operation mode	"△"	Cap Color
No Letter	Momentary	R	Red
Z	Latching	G	Green
		Y	Yellow
		B	Blue
		W	White

SPECIFICATIONS:

- Switch Rating: AC220V/0.5A, DC110V/0.1A.
- Mechanical Life: Momentary ≥200,000cycles; Latching ≥100,000cycles.
- Electrical Life: ≥50,000cycles.
- Contact Resistance: ≤50mΩ.
- Insulation Resistance: ≥100MΩ.
- Dielectric Strength:
Between terminals of the same pole: AC 1,500V, RMS 50Hz, 1min;
Between terminals of different pole: AC 2,000V, RMS 50Hz, 1min.
- Operating Temperature: -25°C ~ +55°C (No Freezing).
- Operating Force: About 1.4N.
- Operating Travel: About 3mm.
- Terminal Type: Pin Terminal(1.8 x 0.4mm), LED Pin(1.8 x 0.3mm).
- IP Class: IP40.

MATERIALS:

- Contact: Silver alloy.
- Button: PC.
- Body: PC.
- Base: PBT.

BRAND 品牌 ONPOW	红波按钮制造有限公司 ONPOW PUSH BUTTON MANUFACTURE CO.,LTD.			
	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ONPOW PUSH BUTTON MANUFACTURE CO.,LTD. AND SHALL NOT BE REPRODUCED COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ONPOW PUSH BUTTON MANUFACTURE CO.,LTD.	USED 用途	APPD 审核 CH 2020/04/28	DR. 制图 ZPD 2020/04/28
FINISH 处理	SCALE 比例 1.5 / 1	UNIT 单位 mm	CHKD 校对 NCH 2020/04/28	DR. 制图 ZPD 2020/04/28
DIMENSIONS 0.00 TO 18.00mm 18.01 TO 30.00mm 30.01 TO 50.00mm 50.01 TO 80.00mm	TOLERANCE ±0.43mm ±0.52mm ±0.62mm ±0.74mm	TITLE 名称 LAS3 Series Pushbutton Switches		SIZE 图纸 A4
DWG NO. 图号 LAS3F不带灯		FILE NAME 档案名称 LAS3F.DWG	SHEET 张 1 / 1	REV. 更改 1