


PANEL CUTOUT
MAX.PANEL THICKNESS
10 mm



Seal Ring

REV. 更改	DESCRIPTION 说明	ENG. 修改人	APPROVE 审核
------------	-------------------	-------------	---------------

SPECIFICATIONS:

- Rating: 2A/36VDC
0.5A/220V.
- Electrical Life: ≥200,000cycles.
- Contact Resistance: ≤50mΩ.
- Insulation Resistance: ≥1,000MΩ.
- Dielectric Strength: 2,000V AC 50Hz 5 Seconds.
- Operating Temperature: -25℃ ~ +55℃ (No Freezing).
- Operating Force: About 4N.
- Torque: 0.6Nm max.applied to nut.
- Contact Configuration: 1NO.
- Operation Type: Momentary.
- The Front Shape:Domed .
- IP Class: IP65,IK09.

MATERIALS:

- Contact: Silver alloy.
- Button:Stainless Steel.
- Body: Nickel Plated Brass /Stainless Steel.
- Base: PBT.

Part Number: GQ19B-10 / J / ◎

"◎"	Crust Material
N	Nickel Plated Brass
S	Stainless Steel
A	Al Alloy(BLACK)

中国·红波按钮制造有限公司
ONPOW PUSH BUTTON MANUFACTURE CO.,LTD.

USED 用途	APPD 审核
FINISH 处理	CHKD 校对
SCALE 比例 1.6 / 1	UNIT 单位 mm
TITLE 名称 Anti-vandal push button	DR. 制图
MATERIAL	DWG NO. 图号 GQ19B-10 / J / ◎
FILE NAME 档案名称 GQ19B-10J◎.DWG	SHEET 张 1 / 1
	REV. 更改 1

SIZE
图纸 A4