




COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
2	RE-E-08445	M.K	A.A	02.02.22					



NOTES
 1 INTERFACE DIMENSIONS CONFORM TO USB2.0 STANDARDS. (Mini-B)
 2 COMPONENTS OF REF. NO. ③ AND ④ ARE APPENDED PRODUCTS.
 3 THE DIAMETER OF A CABLE SHOULD FOLLOW φ 3.5 TO φ 4.0 AS A GUIDE.
 (IT CHANGES A LITTLE WITH HARDNESS OF A SHEATH ETC.)

NO.	COPPER ALLOY	SELECTED GOLD PLATING	4	STELL	TIN ALLOY PLATING
1	PBT	BLACK UL94V-0	3	STELL	TIN ALLOY PLATING
NO.	MATERIAL	FINISH, REMARKS	NO.	MATERIAL	FINISH, REMARKS
CODE NO. (OLD)		DRAWN		DESIGNED	CHECKED
		T. SAKAIZAWA		M. KENJO	A. SUZUKI
		01.09.14		01.09.14	01.09.14
SCALE		PART NO.		APPROVED	RELEASED
5 : 1		EDC3-123212		S. KIKUTA	
UNITS		HIROSE ELECTRIC CO., LTD		UX40-MB-5P	
mm		CL240-0004-7		1/1	