



- NOTES:
1. ALL DIMENSIONS IN MM [INCH]
 2. GENERAL TOLERANCE: X.X = ± 0.4
X.XX = ± 0.25
 3. TERMINAL NUMBERS FOR REF. ONLY
 - ▲ 4. CONTACT RATING: 50mA @ 12VDC
 5. TRAVEL: 0.30 ± 0.15mm
 6. OPERATING FORCE: 260 ± 50mm
 7. CONTACT RESISTANCE: 100mΩ MAX.
 8. ELECRTICAL LIFE: 100,000 CYCLES
 9. ▲ DENOTES CRITICAL PARAMETER
 10. 2011/65/EU (ROHS) COMPLIANT
 11. CONTACT MATERIAL: SILVER
 - ▲ 12. PACKAGE: 450 PIECES PER POLYBAG

F	23971	drawing update	8/8/19	MW
E	20797	CHANGE ACTUATOR TAB ORIENTATION	10/01/12	EBP
D	19578	CHANGED DIMS was 3.9, 14.1, 6.0	1/12/11	BGL
REV	PCR NO	DESCRIPTION	DATE	BY



TITLE TL1100FF160Q				
SCALE	DATE	DR	DWG	REV
3:1	1/12/2011	BGL	P001101	F

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED