



HIRSCHMANN

A BELDEN BRAND

Product information STAS 3 N grau/grey

Industrial Connecting Solutions:Rectangular Connectors:Power Connectors (ST series):Cable plug:STAS 3 N grau/grey

<http://www.e-catalog.beldensolutions.com/link/57078-24228-256261-24351-24355-36006/en/conf/ui/state>

Name		STAS 3 N grau/grey
		
		Cable plug with strain relief
Delivery informations		
Availability		available
Product description		
Description		Cable plug with strain relief
Type		STAS 3 N grau/grey
Order No.		932 143-106
Type of contact		male
Number of contacts		3 + PE
Cable gland		PG 11
Cable diameter		6 mm to 10 mm
Conductor size		max. 1.5 mm ²
Housing Color		grey
Contact bearer color		black
Technical data		
Pin dimensions		2 mm
Rated voltage		AC 400 V / DC 250 V
Rated current		DC 10 A / AC 16 A
Contact resistance		<= 5 mOhm
Type of termination		screw
Material		
Contact material		Cu Zn
Contact surface material		Sn
Contact bearer material		PA
Housing material		PA
Environmental conditions		
Protection class (IEC 60529)		IP 54
Pollution severity		3
Temperature range		-30 °C to +90 °C
Inflammability class		
Housing		UL 94 HB
Contact bearer		UL 94 V-0
Approvals		
UL		UL
VDE		VDE
SEV		SEV
Packing unit		
Packaging unit		100 pieces
Scope of delivery and accessories		
Accessories to order separately		safety brackets STASI 3, order no. 732 045-001



HIRSCHMANN


A Belden BRAND

Industrial Connecting Solutions: Rectangular Connectors: Power Connectors (ST series): Cable plug: STAS 3 N grau/grey

<http://www.e-catalog.beldensolutions.com/link/57078-24228-256261-24351-24355-36006/en/conf/ui/state>

Picture

Drawing



Belden Deutschland GmbH

Im Gewerbepark 2
58579 Schalksmühle
Germany
Phone: +49 7127/14-1806
E-Mail: icos-sales@belden.com

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.