

POS15100D series

15V / 1A (peek 2A) Desktop type AC/DC adaptor



■ Features:

- Universal AC input / Full range
- ErP step II / CEC level VI compliance
- No load power consumption $P < 0.075W$
- Protections: Overload / Short circuit / Over Voltage



ELECTRICAL SPECIFICATION



MODEL	POSB 15100D
OUTPUT	
Rated Voltage	15V
Rated Current	1A (peek 2A)
Current Range	0 ÷ 1A
Rated Power	15W
Line Regulation	± 1%
Load Regulation	± 5%
Tolerance	± 8%
Ripple & Noise (max.)	200mV _{p-p}
Setup, Rise Time	5000ms, 20ms / 230VAC at full load
Hold up Time (typ.)	4ms / 230VAC at full load
INPUT	
Voltage Range	90 ÷ 264VAC
Frequency Range	47 ÷ 63Hz
Efficiency (typ.)	84.13%
AC Current (typ.)	0.45A / 230VAC
No load Power Consumption (max.)	0.1W

PROTECTIONS	
Overload	Range: $2.A \leq OCP \leq 4.A$ Type: hiccup mode, auto-recovery.
Short Circuit	Type: hiccup mode, auto-recovery.
Over Voltage	Type: auto-recovery.

POS15100D series

15V / 1A (peak 2A) Desktop type AC/DC adaptor



WORKING ENVIRONMENT

Working Temperature	0°C ÷ 55°C
Working Humidity	5 ÷ 90% RH non-condensing
Storage Temperature and Humidity	-20°C ÷ 85°C, 5 ÷ 90% RH non-condensing


SAFETY and EMC REGULATIONS

Safety Standards	Compliance to EN 62368-1
Withstand Voltage	IN/OUT: 3.0kVAC
Isolation Resistance	IN/OUT: 20MΩ/500VDC/25°C/70%
EMC Emission	Compliance to EN55032
EMC Immunity	Compliance to EN55024
Harmonic Current	Compliance to EN61000-3-3; EN61000-3-2

OTHERS

AC Inlet	IEC320-C8
DC wire and plug	Wire: 24AWG*2C, length = 1500mm Plug: 2.1/5.5, positive inside
Net Weight / Dimensions	126g / 85.37 x 47.37 x 28.5mm (L x W x H)

MECHANICAL SPECIFICATION




POS15100D series

15V / 1A (peak 2A) Desktop type AC/DC adaptor



MECHANICAL SPECIFICATION



1. All parameters NOT specially mentioned are measured at 230VAC input, rated load and 25°C of ambient temperature.
2. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1 μ F i 47 μ F parallel capacitor.
3. Tolerance includes set up tolerance, line regulation and load regulation.
4. Setup and rise time is measured from 0 to 90% rated output voltage.
5. Power supply is considered as component not indented to apply by end-user. Power supply meets safety and EMC standards however the final equipment with power supply must be re-quality to comply with EMC Directives.