

Product data sheet

Specifications



Exiway Easyled - emergency light block - std - non-maintained - 1 h - 120 lm

OVA38360

Main

Range	Exiway
Product name	Exiway Easyled
Product or component type	Emergency light fitting
Device application	Lighting
Function	Standard
Supply	Non-maintained
Number of batteries	1 x 4.8 V 0.8 Ah Ni-Cd (Nickel-Cadmium)
Colour	White
Light source	LED integral LED 8 W
Light source colour	White
Cover type	Transparent
Wiring device additional information	Can be inhibited with rest mode via Teleur range of remote controls

Complementary

Range compatibility	TBS remote control
[Ue] rated operational voltage	220...230 V AC 50/60 Hz
Power consumption in VA	2.5 VA
Power consumption in W	1.6 W
Current consumption	10 mA
Electrical insulation class	Class II
Autonomy	1 h
Charging time	12 h
Type of glass	Serigraphed transparent glass
Device mounting	Surface ceiling Flush false ceiling Flush wall Surface wall
Material	Housing: plastic Cover: plastic
Height	116 mm
Depth	37 mm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Width	292 mm
Net weight	0.5 kg

Environment

IP degree of protection	IP65
IK degree of protection	IK07
Fire resistance	850 °C
Product certifications	ENEC
Ambient air temperature for operation	0...40 °C
Standards	EN/IEC 60598-2-22 IEC 60695-2-10

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	535.0 g
Package 1 Height	11.7 cm
Package 1 width	3.8 cm
Package 1 Length	29.3 cm
Unit Type of Package 2	S03
Number of Units in Package 2	12
Package 2 Weight	6.907 kg
Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Contractual warranty

Warranty	18 months
----------	-----------