

Product data sheet

Specifications



Unica extend - Schuko trailing lead - 3 gangs - with USB port - white

ST943U3W

Main

Range	Unica
Product or component type	Trailing lead
Aesthetic name	Unica extend
Shape	Square
Control type	Mains switch
Socket number	3
Number of power socket outlets	3 square
Integrated connection type	2 USB port 5 V DC, maximum load current: 2.4 A
Colour tint	White (RAL 9003)
Cable length	3 m

Complementary

Number of socket outlets with earth pin	3
Type of USB power supply	USB type A + A
Number of USB connection	2
[Ue] rated operational voltage	250 V
On/Off switch present	True
[In] rated current	16 A
Outlet poles configuration	2P + E
Outlet standard	Schuko
Socket additional information	Shuttered
Maximum switching capacity	16 A
Pilot light	ON indicator
Material	PP (polypropylene)
Length	254 mm
Width	57 mm
Depth	40.5 mm
Quantity per set	Set of 1

Type of packing	Blister
Surface treatment	Untreated

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	624.0 g
Package 1 Height	9 cm
Package 1 width	5.5 cm
Package 1 Length	32.5 cm
Unit Type of Package 2	S03
Number of Units in Package 2	12
Package 2 Weight	8.2 kg
Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm
Unit Type of Package 3	P06
Number of Units in Package 3	96
Package 3 Weight	74.1 kg
Package 3 Height	77 cm
Package 3 width	80 cm
Package 3 Length	60 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information