

Product data sheet

Specifications



Unica extend - Schuko trailing lead - 3 gangs - with USB port - aluminium/white

ST943U1WA

Main

Range	Unica
Product or component type	Trailing lead
Aesthetic name	Unica extend
Shape	Square
Control type	Mains switch
Socket number	3
Number of power socket outlets	3 square
Integrated connection type	2 USB port 5 V DC, maximum load current: 2.4 A
Cable length	1.5 m
Colour tint	Aluminium/white

Complementary

Number of socket outlets with earth pin	3
Number of USB connection	2
[Ue] rated operational voltage	250 V
[In] rated current	16 A
Outlet poles configuration	2P + E
On/Off switch present	True
Outlet standard	Schuko
Socket additional information	Shuttered
Maximum switching capacity	16 A
Pilot light	ON indicator
Material	PC PP (polypropylene)
Length	254 mm
Width	57 mm
Depth	40.5 mm
Quantity per set	Set of 1
Type of packing	Blister

Colour	Aluminium/white
Surface treatment	Untreated

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	518 g
Package 1 Height	4.5 cm
Package 1 width	13.6 cm
Package 1 Length	33 cm
Unit Type of Package 2	S03
Number of Units in Package 2	16
Package 2 Weight	8.78 kg
Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm
Unit Type of Package 3	P06
Number of Units in Package 3	128
Package 3 Weight	68.36 kg
Package 3 Height	75 cm
Package 3 width	60 cm
Package 3 Length	80 cm

Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information