

# Product data sheet

Specifications



## New Unica, 3 German socket-outlet, 2P+E + shutters, 16A 250V, IP21 D, aluminium

NU307630

### Main

Range	New Unica
Device application	Power supply
Product or component type	Socket-outlet
Device presentation	Mechanism
Socket number	3
Outlet poles configuration	2P
Outlet standard	Schuko
Outlet standard description	Side earth
Ground lug position	45° ground lug
Condition of use	Indoor

### Complementary

Cover type	With shutter
Device mounting	Flush
Rated current	16 A
[Ue] rated operational voltage	250 V
Network type	AC
Network frequency	50/60 Hz
Number of modules	6 modules
Fixing mode	Clip-in
Colour tint	Aluminium
Connections - terminals	Screwless terminals
Cable cross section	0...2.5 mm <sup>2</sup> cable(s), 2 - cable stiffness: flexible 0...2.5 mm <sup>2</sup> cable(s), 2 - cable stiffness: rigid
Minimum load breaking capacity	100 operations 1.25 I <sub>n</sub> and 1.1 U <sub>n</sub> , cos phi = 0.6
Electrical durability	5000 cycles, cos phi = 0.8
Insulation resistance	> 5 MOhm at 500 V
Dielectric strength	2000 V
Material	PC: mechanism cover PC (polycarbonate) GF10 FR: casing

<b>Surface finish</b>	Painted
<b>Quantity per set</b>	Set of 1 flow-pack
<b>Standards</b>	IEC 60884-1
<b>Product certifications</b>	SEMKO DEMKO EAC
<b>Embedding depth</b>	30 mm
<b>Depth</b>	39.4 mm
<b>Width</b>	45 mm
<b>Height</b>	135 mm
<b>Net weight</b>	0.106 kg
<b>Surface treatment</b>	Painted
<b>Resistance to chemical agents</b>	Resistant to alcohol (70 %) Resistant to alcohol (96 %) Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner Resistant to hydrogen peroxide 10 volumes Resistant to hexane

## Environment

<b>Ambient air temperature for operation</b>	-5...35 °C
<b>Ambient air temperature for storage</b>	-5...50 °C
<b>IK degree of protection</b>	IK04
<b>IP degree of protection</b>	IP21D
<b>Environmental characteristic</b>	Acetone Bleach UV resistant Petrol Oil Alcohol Window-cleaning fluid Liquid soap

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Weight</b>	91.0 g
<b>Package 1 Height</b>	4.35 cm
<b>Package 1 width</b>	4.5 cm
<b>Package 1 Length</b>	13.5 cm
<b>Unit Type of Package 2</b>	BB1
<b>Number of Units in Package 2</b>	10
<b>Package 2 Weight</b>	1.045 kg
<b>Package 2 Height</b>	12 cm
<b>Package 2 width</b>	17.5 cm
<b>Package 2 Length</b>	26 cm
<b>Unit Type of Package 3</b>	P06
<b>Number of Units in Package 3</b>	320

Package 3 Weight	44.752 kg
Package 3 Height	77 cm
Package 3 width	80 cm
Package 3 Length	60 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	<a href="#">Product Environmental Profile</a>