


Product data sheet

Specifications



New Unica - 2 German socket-outlet - 2P+E + shutters - 16A 250V - IP21 D - beige

NU206744

Main

| | |
|-----------------------------|------------------|
| Range | New Unica |
| Device application | Power supply |
| Product or component type | Socket-outlet |
| Aesthetic name | Unica Studio |
| Device presentation | Complete product |
| Socket number | 2 |
| Outlet poles configuration | 2P + E |
| Outlet standard | Schuko |
| Outlet standard description | Side earth |

Complementary

| | |
|--------------------------------|---|
| Cover type | With shutter |
| Device mounting | Flush |
| Rated current | 16 A |
| [Ue] rated operational voltage | 250 V |
| Network type | AC |
| Network frequency | 50/60 Hz |
| Fixing mode | Screws |
| Colour tint | Beige (RAL 1013) |
| Connections - terminals | Screw terminals |
| Cable cross section | 0...2.5 mm ² cable(s), 2 - cable stiffness: flexible 0...2.5 mm ² cable(s), 2 - cable stiffness: rigid |
| Minimum load breaking capacity | 100 operations 1.25 I _n and 1.1 U _n , cos phi = 0.6 |
| Electrical durability | 10000 cycles, cos phi = 0.8 |
| Insulation resistance | > 5 MOhm at 500 V |
| Dielectric strength | 2000 V |
| Material | PC: mechanism cover |
| Surface finish | Glossy |
| Quantity per set | Set of 1 flow-pack |
| Standards | IEC 60884-1 |

UNE 20315-1-1
UNE 20315-1-2
DIN VDE 0620-1

| | |
|--------------------------------------|---|
| Product certifications | AENOR EAC |
| Embedding depth | 24 mm |
| Depth | 47 mm |
| Width | 85 mm |
| Height | 125 mm |
| Net weight | 0.099 kg |
| Surface treatment | Untreated |
| Resistance to chemical agents | Resistant to alcohol (70 %) Resistant to alcohol (96 %) Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner Resistant to hydrogen peroxide 10 volumes Resistant to hexane |

Environment

| | |
|--|---|
| Ambient air temperature for operation | -5...35 °C |
| Ambient air temperature for storage | -5...50 °C |
| IK degree of protection | IK04 |
| IP degree of protection | IP21D |
| Environmental characteristic | Acetone Bleach UV resistant Petrol Oil Alcohol Window-cleaning fluid Liquid soap |

Packing Units

| | |
|-------------------------------------|-----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 100.0 g |
| Package 1 Height | 5 cm |
| Package 1 width | 8 cm |
| Package 1 Length | 13 cm |
| Unit Type of Package 2 | P06 |
| Number of Units in Package 2 | 180 |
| Package 2 Weight | 33.308 kg |
| Package 2 Height | 75 cm |
| Package 2 width | 80 cm |
| Package 2 Length | 60 cm |
| Unit Type of Package 3 | S04 |
| Number of Units in Package 3 | 45 |
| Package 3 Weight | 6.327 kg |
| Package 3 Height | 30 cm |

| | |
|-------------------------|-------|
| Package 3 width | 40 cm |
| Package 3 Length | 60 cm |

Offer Sustainability

| | |
|--------------------------|---|
| EU RoHS Directive | Under investigation |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
