

Product data sheet

Specifications



SCHUKO sock.-out. w. hng.lid, IP44, shut., screwl. term., anthracite, Sys. Des.

MTN2314-6034

Main

Range of product	Merten System Design
Aesthetic name	System Design
Product or component type	Socket-outlet

Complementary

Device presentation	Complete product
Device mounting	Flush
Outlet poles configuration	2P + E
Outlet standard description	Side earth
Outlet standard	Schuko
Socket number	1
Cover type	Hinged lid With shutter
Rated current	16 A
Number of gangs	1 gang
Colour tint	Anthracite
Fixing mode	By screws and claws
[Ue] rated operational voltage	250 V
Material	PC (polycarbonate) matt
Connections - terminals	Screwless terminals
Length	71 mm
Height	45 mm
Width	71 mm

Environment

Surface treatment	Varnished
Standards	DIN 49440
IP degree of protection	IP44

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	115.0 g
Package 1 Height	5.3 cm
Package 1 width	7.6 cm
Package 1 Length	7.6 cm
Unit Type of Package 2	CAR
Number of Units in Package 2	50
Package 2 Weight	6.155 kg
Package 2 Height	19 cm
Package 2 width	30 cm
Package 2 Length	40 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins