

# Product data sheet

Specifications



## SpaceLogic KNX Universal Dimmer Master 2 channel

MTN6710-0102

### Main

Range of product	SpaceLogic KNX
Product or component type	Dimming actuator
Operating mode	KNX bus system
Bus type	KNX

### Complementary

Mounting support	DIN rail
[Ue] rated operational voltage	230 V
Network frequency	50/60 Hz
Number of outputs	2
Load type	LV halogen: 20...350 W at 230 V Incandescent lamp: 20...350 W at 230 V Halogen lamp: 20...350 W at 230 V RC LED lamp: 2...200 W at 230 V RL LED lamp: 2...60 W at 230 V

### Environment

IP degree of protection	IP20
-------------------------	------

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	264.0 g
Package 1 Height	8.4 cm
Package 1 width	12.8 cm
Package 1 Length	15.9 cm
Unit Type of Package 2	S04
Number of Units in Package 2	28
Package 2 Weight	8.193 kg
Package 2 Height	30 cm
Package 2 width	40 cm
Package 2 Length	60 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>

## Contractual warranty

Warranty	18 months
----------	-----------