

Product data sheet

Specifications



New Unica - pull string switch - 2 modules - screwless terminals - aluminium

NU322630

Main

Range	New Unica
Product or component type	Pull string switch
Device presentation	Mechanism
Device application	Control
Switch function	1-pole 2-way
Rated current	10 A
Actuator	Cord push-button
Number of modules	2 modules
Fixing mode	Clip-in
Colour tint	Aluminium

Complementary

Technology type	Electromechanical
Cable length	1 m
[Ue] rated operational voltage	250 V
Network type	AC
Network frequency	50/60 Hz
Opening distance	> 3 mm
Connections - terminals	Screwless terminals
Cable cross section	2.5 mm ² flexible cable 2.5 mm ² rigid cable
Minimum load breaking capacity	200 operations 1.25 I _n and 1.1 U _n , cos phi = 0.3
Electrical durability	20000 cycles, cos phi = 0.6
Dielectric strength	2000 V
Insulation resistance	> 5 MOhm at 500 V
Material	Thermoplastic ABS-UV stabilised: mechanism rocker PC (polycarbonate) GF10 FR: casing CuZn37: terminals PBT (polybutylene terephthalate) GF30: release button
Standards	IEC 60669-1
Directives	2014/35/EU - low voltage directive

Product certifications	CE NF AENOR EAC
Ambient air temperature for operation	-5...40 °C
Ambient air temperature for storage	-5...50 °C
Embedding depth	21.15 mm
Depth	47 mm
Width	45 mm
Height	45 mm
Net weight	0.035 kg
Surface treatment	Painted
Surface finish	Brilliant
Resistance to chemical agents	Resistant to alcohol (70 %) Resistant to alcohol (96 %) Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner Resistant to hydrogen peroxide 10 volumes Resistant to hexane

Environment

IK degree of protection	IK04
IP degree of protection	IP21D

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	38.0 g
Package 1 Height	4.5 cm
Package 1 width	5 cm
Package 1 Length	7 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	463.0 g
Package 2 Height	8 cm
Package 2 width	18 cm
Package 2 Length	18.5 cm
Unit Type of Package 3	S02
Number of Units in Package 3	20
Package 3 Weight	1.233 kg
Package 3 Height	15 cm
Package 3 width	30 cm
Package 3 Length	40 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins