

# Product data sheet

Specifications



## Pull string switch, New Unica, 2 modules, 10 A, 250 V, AC, beige

NU322644

### Main

Range	New Unica
Product or component type	Pull string switch
Aesthetic name	Unica (standard aesthetic)
Device presentation	Mechanism
Device application	Control
Switch function	1-pole 2-way
Rated current	10 A
Actuator	Cord push-button
Number of modules	2 modules
Fixing mode	Clip-in
Colour tint	Beige (RAL 1013)

### Complementary

Technology type	Electromechanical
Cable length	1 m
[Ue] rated operational voltage	250 V
Network type	AC
Network frequency	50/60 Hz
Opening distance	> 3 mm
Connections - terminals	Screwless terminals
Cable cross section	2.5 mm <sup>2</sup> flexible cable 2.5 mm <sup>2</sup> rigid cable
Minimum load breaking capacity	200 operations 1.25 I <sub>n</sub> and 1.1 U <sub>n</sub> , cos phi = 0.3
Electrical durability	40000 cycles, cos phi = 0.6
Dielectric strength	2000 V
Insulation resistance	> 5 MOhm at 500 V
Material	ASA + PC: mechanism cover Thermoplastic ABS-UV stabilised: mechanism rocker PC (polycarbonate) GF10 FR: casing CuZn37: terminals PBT (polybutylene terephthalate) GF30: release button
Standards	IEC 60669-1

<b>Directives</b>	2014/35/EU - low voltage directive
<b>Product certifications</b>	EAC AENOR NF CE
<b>Ambient air temperature for operation</b>	-5...40 °C
<b>Ambient air temperature for storage</b>	-5...50 °C
<b>Embedding depth</b>	21.15 mm
<b>Depth</b>	47 mm
<b>Width</b>	45 mm
<b>Height</b>	45 mm
<b>Net weight</b>	0.0291 kg
<b>Surface treatment</b>	Untreated
<b>Surface finish</b>	Glossy
<b>Resistance to chemical agents</b>	Resistant to alcohol (70 %) Resistant to alcohol (96 %) Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner Resistant to hydrogen peroxide 10 volumes Resistant to hexane

## Environment

<b>IK degree of protection</b>	IK04
<b>IP degree of protection</b>	IP20
<b>Environmental characteristic</b>	Acetone Oil UV resistant Liquid soap Window-cleaning fluid Bleach Alcohol Petrol

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Weight</b>	32.0 g
<b>Package 1 Height</b>	3.5 cm
<b>Package 1 width</b>	4.5 cm
<b>Package 1 Length</b>	4.5 cm
<b>Unit Type of Package 2</b>	BB1
<b>Number of Units in Package 2</b>	10
<b>Package 2 Weight</b>	404.0 g
<b>Package 2 Height</b>	8.2 cm
<b>Package 2 width</b>	17.7 cm
<b>Package 2 Length</b>	18.5 cm
<b>Unit Type of Package 3</b>	S02
<b>Number of Units in Package 3</b>	20

<b>Package 3 Weight</b>	1.123 kg
<b>Package 3 Height</b>	15 cm
<b>Package 3 width</b>	30 cm
<b>Package 3 Length</b>	40 cm

## Offer Sustainability

<b>Sustainable offer status</b>	Green Premium product
<b>REACH Regulation</b>	<a href="#">REACH Declaration</a>
<b>REACH free of SVHC</b>	Yes
<b>EU RoHS Directive</b>	Compliant <a href="#">EU RoHS Declaration</a>
<b>Toxic heavy metal free</b>	Yes
<b>Mercury free</b>	Yes
<b>RoHS exemption information</b>	<a href="#">Yes</a>
<b>China RoHS Regulation</b>	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
<b>Environmental Disclosure</b>	<a href="#">Product Environmental Profile</a>