

# Product data sheet

Specifications



## New Unica - pull string switch - 2 modules -screwless terminals - anthracite

NU322654

### Main

Range	New Unica
Product or component type	Pull string switch
Device presentation	Mechanism
Device application	Control
Switch function	1-pole 2-way
Rated current	10 A
Actuator	Cord push-button
Number of modules	2 modules
Fixing mode	Clip-in
Colour tint	Anthracite (RAL 7021)

### Complementary

Technology type	Electromechanical
Cable length	1 m
[Ue] rated operational voltage	250 V
Network type	AC
Network frequency	50/60 Hz
Opening distance	> 3 mm
Connections - terminals	Screwless terminals
Cable cross section	2.5 mm <sup>2</sup> flexible cable 2.5 mm <sup>2</sup> rigid cable
Minimum load breaking capacity	200 operations 1.25 I <sub>n</sub> and 1.1 U <sub>n</sub> , cos phi = 0.3
Electrical durability	20000 cycles, cos phi = 0.6
Dielectric strength	2000 V
Insulation resistance	> 5 MOhm at 500 V
Material	Thermoplastic ABS-UV stabilised: mechanism rocker PC (polycarbonate) GF10 FR: casing CuZn37: terminals PBT (polybutylene terephthalate) GF30: release button
Standards	IEC 60669-1
Directives	2014/35/EU - low voltage directive

<b>Product certifications</b>	NF CE AENOR EAC
<b>Ambient air temperature for operation</b>	-5...40 °C
<b>Ambient air temperature for storage</b>	-5...50 °C
<b>Embedding depth</b>	21.15 mm
<b>Depth</b>	47 mm
<b>Width</b>	45 mm
<b>Height</b>	45 mm
<b>Net weight</b>	0.035 kg
<b>Surface treatment</b>	Painted
<b>Surface finish</b>	Matt
<b>Resistance to chemical agents</b>	Resistant to alcohol (70 %) Resistant to alcohol (96 %) Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner Resistant to hydrogen peroxide 10 volumes Resistant to hexane

## Environment

<b>IK degree of protection</b>	IK04
<b>IP degree of protection</b>	IP21D

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Weight</b>	37.0 g
<b>Package 1 Height</b>	4.5 cm
<b>Package 1 width</b>	5 cm
<b>Package 1 Length</b>	7 cm
<b>Unit Type of Package 2</b>	BB1
<b>Number of Units in Package 2</b>	10
<b>Package 2 Weight</b>	460.0 g
<b>Package 2 Height</b>	8 cm
<b>Package 2 width</b>	18 cm
<b>Package 2 Length</b>	18.5 cm
<b>Unit Type of Package 3</b>	S02
<b>Number of Units in Package 3</b>	20
<b>Package 3 Weight</b>	1.23 kg
<b>Package 3 Height</b>	15 cm
<b>Package 3 width</b>	30 cm
<b>Package 3 Length</b>	40 cm

# Offer Sustainability

<b>REACH Regulation</b>	<a href="#">REACH Declaration</a>
<b>REACH free of SVHC</b>	Yes
<b>EU RoHS Directive</b>	Compliant <a href="#">EU RoHS Declaration</a>
<b>Toxic heavy metal free</b>	Yes
<b>Mercury free</b>	Yes
<b>RoHS exemption information</b>	<a href="#">Yes</a>
<b>China RoHS Regulation</b>	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
<b>WEEE</b>	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins