



New Unica - Roller blind push-button switch 6A screwless 2modules white

NU320718

Main

| Range of product | New Unica |
|---------------------------|-------------------|
| Product or component type | Shutter control |
| Device presentation | Mechanism |
| Technology type | Electromechanical |
| Number of rocker | 2 |
| Device application | Control |
| Colour tint | White (RAL 9003) |
| Type of packing | Flow-pack |

| Complementary | |
|---|--|
| Rated current | 6 A |
| [Ue] rated operational voltage | 250 V |
| Network type | AC |
| Network frequency | 50/60 Hz |
| Electrical durability | 20000 cycles, cos phi = 0.6 |
| Insulation resistance | > 5 MOhm at 500 V |
| Dielectric strength | 2000 V |
| Minimum load breaking capacity | 200 operations 1.25 In and 1.1 Un, cos phi = 0.3 |
| Opening distance | > 3 mm |
| Actuator | Rocker |
| Number of modules | 2 modules |
| Connections - terminals | Screwless terminals |
| Cable cross section | 02.5 mm² rigid cable 02.5 mm² flexible cable |
| Material | CuZn15: terminals Thermoplastic ABS-UV stabilised: mechanism rocker PC (polycarbonate) GF10 FR: casing PBT (polybutylene terephthalate) GF30: release button |
| Marking | Arrow |
| Surface finish | Glossy |
| Specific treatment - integrated within the material | Untreated |

| Fixing mode | Clip-in |
|---------------------------------------|--|
| Width | 45 mm |
| Height | 45 mm |
| Depth | 44.35 mm |
| Embedding depth | 32.8 mm |
| Net weight | 0.0331 kg |
| Ambient air temperature for operation | -540 °C |
| Ambient air temperature for storage | -550 °C |
| Standards | LV directive IEC 60669-1 |
| Product certifications | CE AENOR EAC NF VDE |
| Resistance to chemical agents | Resistant to alcohol (70 %) Resistant to alcohol (96 %) Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner Resistant to hydrogen peroxide 10 volumes Resistant to hexane |

Environment

| IP degree of protection | IP4X |
|------------------------------|--|
| IK degree of protection | IK04 |
| Environmental characteristic | Oil UV resistant Acetone Liquid soap Window-cleaning fluid Petrol Alcohol Bleach |

Packing Units

| Unit Type of Package 1 | PCE |
|------------------------------|----------|
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 39.0 g |
| Package 1 Height | 4.5 cm |
| Package 1 width | 4.5 cm |
| Package 1 Length | 4.5 cm |
| Unit Type of Package 2 | BB1 |
| Number of Units in Package 2 | 10 |
| Package 2 Weight | 468.0 g |
| Package 2 Height | 7.6 cm |
| Package 2 width | 18 cm |
| Package 2 Length | 18.6 cm |
| Unit Type of Package 3 | S03 |
| Number of Units in Package 3 | 80 |
| Package 3 Weight | 4.166 kg |

| Package 3 Height | 30 cm |
|----------------------------|---|
| Package 3 width | 30 cm |
| Package 3 Length | 40 cm |
| Offer Sustainability | |
| Sustainable offer status | Green Premium product |
| REACh Regulation | REACh Declaration |
| REACh free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope) |
| Environmental Disclosure | Product Environmental Profile |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |